

# CWNA-106<sup>Q&As</sup>

Certified Wireless Network Administrator

**Pass CWNP CWNA-106 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/cwna-106.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

What distinguishes an independent basic service set (IBSS) from an infrastructure basic serviceset (BSS)?

- A. An IBSS does not have a distribution system (DS), but a BSS does.
- B. An IBSS does not require beacon frames, but a BSS does.
- C. An IBSS does not support 802.11 authentication or association, but a BSS does.
- D. An IBSS does not support any 802.11ac enhancements, but a BSS does.

Correct Answer: A

---

### QUESTION 2

ABC Company performs government contract work that requires disabling WLANs and has recently purchased an 802.11 Wireless Intrusion Prevention System (WIPS) to enforce their "NO WIRELESS" network security policy.

What attack type cannot be recognized by the WIPS?

- A. Deauthentication
- B. Rogue APs installation
- C. Layer 3 DoS
- D. Packet capturing
- E. RF jamming

Correct Answer: D

---

### QUESTION 3

What mechanisms are specified by the IEEE 802.11 standard to attempt to prevent multiple radios from transmitting on the RF medium at a given point in time? (Choose 3)

- A. Random backoff timer
- B. Clear channel assessment
- C. Network allocation vector
- D. Slot assessment value
- E. Collision detection

Correct Answer: ABC

---

**QUESTION 4**

In an enterprise WLAN, what condition will prevent a dual-band VHT/HT client device from performing a fast and seamless transition (i.e. latency-sensitive applications are not disrupted) between two access points that are managed by the same WLAN controller?

- A. The current AP is using channel 1 and the new AP is using channel 40.
- B. The SSID of the current AP does not match the SSID of the new AP.
- C. The current AP supports only HT and the new AP is VHT capable.
- D. The access points are hiding the SSID in Beacons and Probe Response frames.

Correct Answer: B

---

**QUESTION 5**

What component of the 802.11 standard allows stations to reserve access to the RF medium for a specified period of time?

- A. Short guard intervals
- B. DTIM Interval
- C. Listen Interval
- D. Probe Request frames
- E. RTS or CTS frames

Correct Answer: E

[Latest CWNA-106 Dumps](#)

[CWNA-106 PDF Dumps](#)

[CWNA-106 Brindumps](#)