

CWNA-107^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-107 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/cwna-107.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

What statement about the IEEE 802.11-2016 QoS facility is true?

- A. 802.11 QoS is achieved by giving high priority queues a statistical advantage at winning contention.
- B. Four 802.1p user priorities are mapped to eight 802.11 transmit queues.
- C. 802.11 control frames are assigned to the 802.11 EF priority queue.
- D. When the Voice queue has frames awaiting transmission, no data will be transmitted from the Best Effort queue.

Correct Answer: A

QUESTION 2

Which unit of measurement is an absolute unit that is used to quantify received signal power levels on a logarithmic scale?

- A. dBm
- B. SNR
- C. RSSI
- D. VSWR

Correct Answer: A

QUESTION 3

ABC Company is planning to install a new 802.11ac WLAN, but wants to upgrade its wired infrastructure first to provide the best user experience possible. ABC Company has hired you to perform the RF site survey. During the interview with the network manager, you are told that the new Ethernet edge switches will support VoIP phones and 802.11 access points, both using 802.3 PoE.

After hearing this information, what immediate concerns do you note?

- A. The power budget in the edge switches must be carefully planned and monitored based on the number of supported PoE devices.
- B. The edge Ethernet switches should support Ether-channel to get the best results out of the network.
- C. VoIP phones and 802.11 access points should not be powered by the same edge switch due to distortion.
- D. If the switches are in optimal locations for VoIP phones, they are likely to be suboptimal locations for 802.11 APs

Correct Answer: A

QUESTION 4

You administer a WLAN that offers a guest SSID of GUESTNETWORK. Users connect to the GUESTNETWORK SSID, but report that they cannot browse the Internet. The devices simply report no Internet connection. What common problem causes this scenario?

- A. NTP issues
- B. Hardware issues
- C. IP routing issues
- D. Captive portal issues

Correct Answer: C

QUESTION 5

What factor will have the most significant impact on the amount of wireless throughput available to each station within a BSS?

- A. The Layer 3 protocol used by each station to transmit data over the wireless link
- B. The number of client stations associated to the BSS
- C. The power management settings in the access point beacons
- D. The presence of co-located (10m away) access points on non-overlapping channels

Correct Answer: B

[Latest CWNA-107 Dumps](#)

[CWNA-107 Study Guide](#)

[CWNA-107 Brindumps](#)