

CWNA-108^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-108 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/cwna-108.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.pass2lead.com/cwna-108.html

QUESTION 1

You were previously onsite at XYZ\\'s facility to conduct a pre-deployment RF site survey. The WLAN has been deployed according to your recommendations and you are onsite again to perform a post- deployment validation survey.

When performing this type of post-deployment RF site survey voice over Wi-Fi, what is an action that must be performed?

- A. Spectrum analysis to locate and identify RF interference sources.
- B. Frequency-band hopping analysis to detect improper RF channel implementations.
- C. Application analysis with an active phone call on an VoWiFi handset.
- D. Protocol analysis to discover channel use on neighboring APs.

Correct Answer: C

QUESTION 2

Which one of the following 802.11 PHYs is more likely to be used in an industrial deployment but not likely to be used in standard office deployments?

- A. SIG
- B. VHT
- C. OFDM
- D. HT

Correct Answer: B

QUESTION 3

Which IEEE 802.11 physical layer (PHY) specification includes support for and compatibility with both ERP and HR/DSSS?

- A. VHT (802.11ac)
- B. OFDM (802.11a)
- C. DSSS (802.11-Prime)
- D. HT (802.11n)

Correct Answer: D

https://www.pass2lead.com/cwna-108.html

2024 Latest pass2lead CWNA-108 PDF and VCE dumps Download

QUESTION 4

What statement about 802.11 WLAN bridges is true?

- A. WLAN bridges only work in the 2.4 GHz frequency band and they support only SISO communications
- B. WLAN bridges must use a channel with acceptable SNR at both transceivers to maintain the desired data rate bidirectionally
- C. WLAN bridges may support MIMO communications, but only if used in the 5 GHz frequency band
- D. WLAN bridges must be implemented such that no interference occurs on the channel anywhere between the two endpoints used to establish the bridge

Correct Answer: C

QUESTION 5

You have received a report of poor wireless connections on the third floor of a building under your administration. Three individuals have reported the problem. Apparently, the connections are reporting a strong signal, but the users cannot access the Internet. With the problem identified, what is the next logical step in the troubleshooting process?

- A. Verify the solution
- B. Discover the scale of the problem
- C. Perform corrective actions
- D. Create a plan of action or escalate the problem

Correct Answer: B

CWNA-108 VCE Dumps

CWNA-108 Study Guide CWNA-108 Exam Questions