

# DES-4121<sup>Q&As</sup>

PowerEdge Specialist Exam for Implementation Engineer

**Pass EMC DES-4121 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-4121.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

A technician needs to add a device to SupportAssist Enterprise. Policy requires that no additional software be installed on the server OS.

In addition to Username and Password, what information is required to add the device?

- A. IP address or hostname for the server OS
- B. IP address for Dell TechDirect
- C. IP address for OpenManage Server Administrator
- D. IP address or hostname for the iDRAC

Correct Answer: D

---

### QUESTION 2

A user installed OME on a PowerEdge R640 server. OME has discovered and is currently monitoring another 30 remote PowerEdge 14G servers. Each server has the following configuration:

2x CPUs 384 GB RAM 6x 1TB drives in a RAID 6 virtual disk No hot spare drive PERC vFlash iDRAC9 Express license

At 9 PM on Monday evening, one of the remote servers has a disk failure but stays operational. The administrator monitoring OME does not find out about the issue until 5 PM in the following Friday. They place a support call to investigate why OME was not informed about the disk failure before then.

What is the reason for this issue not being reported to OME?

- A. Remote servers are not configured with OME as the trap destination address. OME discovered the issue during a routing status check which is configured to run at 5 PM every Friday.
- B. OME only updates its alert database at 5 PM every Friday.
- C. Remote servers are not configured with OME as the trap destination address. OME was informed of the issue when remote servers sent alerts at 5 PM Friday.
- D. Remote servers need to have the iDRAC Enterprise license installed to be able to send alerts.

Correct Answer: D

---

### QUESTION 3

A technician needs to replace a server component with orange tabs/releases. Which set of paired steps should the technician take to complete this task?

- A. Power off the server Apply anti-static procedures

- B. Remove power cables Cold swap the component
- C. Cold swap the component Apply anti-static procedures
- D. Hot swap the component Apply anti-static procedures

Correct Answer: D

Reference [https://www.sos.state.co.us/pubs/elections/VotingSystems/DVS-DemocracySuite/documentation/Dell\\_Powerededge\\_R630\\_Owner\\_Manual.pdf](https://www.sos.state.co.us/pubs/elections/VotingSystems/DVS-DemocracySuite/documentation/Dell_Powerededge_R630_Owner_Manual.pdf) (84)

---

#### QUESTION 4

What can a technician do to ensure that no malicious code can be introduced into any of the servers through physical access?

- A. Set USB 3.0 to disabled
- B. Set Secure Boot Policy to enabled
- C. Set User Accessible Ports to disabled
- D. Set UEFI Variable Acces to disabled

Correct Answer: C

---

#### QUESTION 5

A technician plugs in a server that has dual power supply units. After powering on the system, they notice that the power supply status indicators blink green then turn off.

What troubleshooting steps should the technician take to resolve this issue?

- A. Set the power supply redundancy option to `No Redundancy\`
- B. Check that the PSUs are not connected to a 240VAC source
- C. Update the iDRAC firmware to enable control of new PSU features
- D. Check that the PSUs are the same efficiency, feature set, health status, and supported voltage

Correct Answer: D

Reference <https://qrl.dell.com/Files/en-us/Html/Manuals/R630/Power%20indicator%20codes=GUIDFBD2281B-1608-4FF8-9AFE-4E33BB6FF810=1=en-us=.html>

[Latest DES-4121 Dumps](#)

[DES-4121 VCE Dumps](#)

[DES-4121 Exam Questions](#)