

DES-4421^{Q&As}

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-4421.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

At the initial release of the MX7000 for a daisy-chained configuration in a multi-chassis management group (MCM) what is the maximum number of member chassis allowed, not counting the lead chassis?

- A. 9
- B. 10
- C. 16
- D. 20

Correct Answer: A

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/omem1.00.01_ug/chassis-groups?guid=guid-967e1786-b148-45f6-8184-c6a70296483a&lang=en-us

QUESTION 2

What is a characteristic of MX7000 networking in Scalable Fabric Mode?

- A. Enabled by default, all switch-specific OS10EE capabilities are available.
- B. Layer 2 bridging is disabled by default and interfaces must join a bridge domain (VLAN) before being to forward frames.
- C. All switch interfaces are assigned to VLAN 1 by default and are in the same Layer 2 bridge domain.
- D. Available on MX9116n FSE and MX7116n FEM but not on the MX5108n.

Correct Answer: D

Reference: <https://hasanmansur.com/2019/01/10/mx7000-networking-part-2-operating-modes-iom-selection/>

QUESTION 3

The MDB chassis tub assembly vertical distribution board provides connectivity to which chassis components?

- A. Five near fan modules
- B. Four cooling fans and four fabric I/O modules
- C. Power supplies, compute sleds, Management Modules, and two fabric I/O modules
- D. Pear power supplies, compute sleds, Management Modules, and all fabric I/O modules

Correct Answer: B

Reference: https://i.dell.com/sites/csdocuments/Product_Docs/en/dell_emc_poweredge_mx7000_technical_guide.pdf

QUESTION 4

DRAG DROP

A technician is deploying a new MX7000 chassis using the Chassis Deployment Wizard.

What is the correct order o steps followed by the wizard?

Select and Place:

Configure iDRAC and IOM Quick Deploy Settings	STEP 1
Import Profile or join Multi-chassis Group	STEP 2
Configure Activity and Alerts	STEP 3
Define Groups	STEP 4
Update Firmware and configure Proxy	STEP 5

Correct Answer:

	Import Profile or join Multi-chassis Group
	Configure Activity and Alerts
	Configure iDRAC and IOM Quick Deploy Settings
	Update Firmware and configure Proxy
	Define Groups

QUESTION 5

DRAG DROP

Match each deployment logical block with its attributes.

Select and Place:

<u>Logical Block:</u>	<u>Attributes:</u>
Network	BIOS, RAID, NIC, iDRAC
Server Template	WWN, WWPN, Virtual MAC Address
Server Configuration Profile	VLAN, QoS
Virtual I/O Pool	Server Template, Virtual I/O Pool and Network

Correct Answer:

<u>Logical Block:</u>	<u>Attributes:</u>
	Server Configuration Profile
	Virtual I/O Pool
	Network
	Server Template

[DES-4421 PDF Dumps](#)

[DES-4421 Practice Test](#)

[DES-4421 Study Guide](#)