

# DES-4421<sup>Q&As</sup>

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

**Pass EMC DES-4421 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-4421.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Refer to the exhibit.



How many internal server-facing ports are available on this I/O module for the MX7000 chassis?

- A. 2
- B. 8
- C. 16
- D. 24

Correct Answer: C

Reference: [https://i.dell.com/sites/csdocuments/Product\\_Docs/en/dell\\_emc\\_poweredge\\_mx7000\\_technical\\_guide.pdf](https://i.dell.com/sites/csdocuments/Product_Docs/en/dell_emc_poweredge_mx7000_technical_guide.pdf)

**QUESTION 2**

DRAG DROP

An administrator is using the OME-M GUI to change the hostname on an unconfigured I/O module inserted in slot A1. They log on to the MX7000 chassis home page.

What is the correct order of steps the administrator should take to set the management IP address?

Select and Place:

Click Apply	STEP 1
Edit the hostname field	STEP 2
Select IOM-A1 in the list	STEP 3
Select Settings and then Management	STEP 4
Select Devices > I/O Modules	STEP 5

Correct Answer:

	Select Devices > I/O Modules
	Select IOM-A1 in the list
	Select Settings and then Management
	Click Apply
	Edit the hostname field

**QUESTION 3**

DRAG DROP

A technician is deploying a new MX7000 chassis using the Chassis Deployment Wizard.

What is the correct order o steps followed by the wizard?

Select and Place:

Configure iDRAC and IOM Quick Deploy Settings	STEP 1
Import Profile or join Multi-chassis Group	STEP 2
Configure Activity and Alerts	STEP 3
Define Groups	STEP 4
Update Firmware and configure Proxy	STEP 5

Correct Answer:

	Import Profile or join Multi-chassis Group
	Configure Activity and Alerts
	Configure iDRAC and IOM Quick Deploy Settings
	Update Firmware and configure Proxy
	Define Groups

**QUESTION 4**

What is a characteristic of MX7000 networking in Scalable Fabric Mode?

- A. Enabled by default, all switch-specific OS10EE capabilities are available.
- B. Layer 2 bridging is disabled by default and interfaces must join a bridge domain (VLAN) before being to forward frames.
- C. All switch interfaces are assigned to VLAN 1 by default and are in the same Layer 2 bridge domain.
- D. Available on MX9116n FSE and MX7116n FEM but not on the MX5108n.

Correct Answer: D

Reference: <https://hasanmansur.com/2019/01/10/mx7000-networking-part-2-operating-modes-iom-selection/>

**QUESTION 5**

In the assigned mapping of the MX5016s storage sled what is an assignment option used for independent storage to be mapped to a compute sled?

- A. Drive-assigned enables the MX5016s to be split among multiple compute sleds. Each compute node only "sees" the disks that are assigned to it and not the others.
- B. Drive-assigned enables the MXG610s to the first eight drives in the MX5016s.
- C. Enclosure-assigned enables the MX5016 to be split among multiple compute sleds. Each compute node only "sees" the disks that are assigned to it and not the others.
- D. Enclosure-assigned enables the MXG610s to the first eight drives in the MX5016s.

Correct Answer: A