

DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You need to configure OSPF on a DNOS 6 switch and have entered the following:

```
Switch-1(config)# ip routing Switch-1(config)# interface vlan 20 Switch-1(config-if-vlan20)# ip address 10.1.20.1 255.255.255.0
```

```
Switch-1(config)# router ospf Switch-1(config-router)# router-id 10.1.1.1
```

Based on the information referenced above, what is missing from the configuration?

- A. area 0 is missing from the ip routing command
- B. ip ospf area 0 is missing from the interface vlan 20 section
- C. router ospf is missing the routing instance
- D. area 0 is missing from the router-id command

Correct Answer: B

QUESTION 2

DRAG DROP

What is the typical sequence of steps to upgrade the firmware of a Dell EMC N-Series switch?

Select and Place:

Copy the firmware image from the TFTP server to the switch	Step 1
Configure and start the TFTP server	Step 2
Update the boot code on the switch and reboot	Step 3
Backup the running-config to a TFTP server	Step 4
Select the new image for the next boot	Step 5

Correct Answer:

	Configure and start the TFTP server
	Backup the running-config to a TFTP server
	Copy the firmware image from the TFTP server to the switch
	Select the new image for the next boot
	Update the boot code on the switch and reboot

QUESTION 3

A switch interface has been properly configured for static port security with one defined allowable MAC address. However, when the network administrator plugs a switch into that port, multiple devices are still allowed access to the network. Where must port security also be enabled to have an effect?

- A. Enabled globally on the switch
- B. Enabled on all attached devices
- C. Enabled on all switches in the network
- D. Enabled on all interfaces of the switch

Correct Answer: A

Reference: <https://www.dell.com/support/article/en-us/how10392/how-to-configure-mac-based-port-security-on-dell-n2000-n3000-and-n4000-series-switches?lang=en>

QUESTION 4

If VoIP traffic uses multiple QoS prioritization schemes, what refers to VoIP traffic?

- A. COS 2, DSCP 22, AF
- B. COS 2, DSCP 46, EF
- C. COS 5, DSCP 42, AF D. COS 5, DSCP 46, EF

Correct Answer: D

QUESTION 5

Which RSTP-PV features are embedded and cannot be disabled?

- A. DirectLink Rapid Convergence and DirectLink Fast Rapid Convergence
- B. IndirectLink Rapid Convergence and IndirectLink Fast Rapid Convergence
- C. DirectLink Rapid Convergence and IndirectLink Fast Rapid Convergence
- D. DirectLink Fast Rapid Convergence and IndirectLink Rapid Convergence

Correct Answer: C

Reference: <https://www.manualslib.com/manual/858353/Dell-Networking-N4000-Series.html?page=724>

[Latest DES-5121 Dumps](#)

[DES-5121 VCE Dumps](#)

[DES-5121 Study Guide](#)