

# DES-5221<sup>Q&As</sup>

Specialist Implementation Engineer Data Center Networking Exam

**Pass EMC DES-5221 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-5221.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

Which commands are required to properly configure an OS10 switch to run OSPF on eth1/1/3 and to add network 144.254.1.0/30 to OSPF area 0?

- A. OS10(config)# interface ethernet 1/1/3 OS10(config-if-eth1/1/3)# no shutdown OS10(config-if-eth1/1/3)# no switchport OS10(config-if-eth1/1/3)# ip address 144.254.1.2/30 OS10(config-if-eth1/1/3)# ip ospf 1 area 0.0.0.0 OS10(config)# router ospf 1
- B. OS10(config)# router ospf 1 OS10(config-router-ospf-1)# router-id 1.1.1.1 OS10(config)# interface ethernet 1/1/3 OS10(config-if-eth1/1/3)# no shutdown OS10(config-if-eth1/1/3)# no switchport OS10(config-if-eth1/1/3)# ip ospf 1 area 0.0.0.0
- C. OS10(config)# interface ethernet 1/1/3 OS10(config-if-eth1/1/3)# no shutdown OS10(config-if-eth1/1/3)# ip address 144.254.1.2/30 OS10(config-if-eth1/1/3)# no switchport OS10(config-if-eth1/1/3)# ip ospf 1 area 0.0.0.0 OS10(config)# router ospf 1
- D. OS10(config)# interface ethernet 1/1/3 OS10(config-if-eth1/1/3)# no shutdown OS10(config-if-eth1/1/3)# ip address 144.254.1.2/30 OS10(config-if-eth1/1/3)# no switchport OS10(config-if-eth1/1/3)# ip ospf 1 area 0.0.0.0 OS10(config-if-eth1/1/3)# router ospf 1

Correct Answer: C

---

### QUESTION 2

When installing OS10 on a switch from a USB drive, what format is used for the file system?

- A. HFS+
- B. FAT32
- C. NTFS
- D. HFS

Correct Answer: B

Reference: <https://www.dell.com/support/article/en-hr/how12762/dell-emc-networking-how-to-update-os10-on-a-switch-running-os10?lang=en>

---

### QUESTION 3

Using the MAC 8c-ec-4b-5b-61-9d, what is a valid EUI-64 link local address?

- A. 2001::a9:8eec:4bff:fc5b:619d
- B. fe80::a9:8cec:4bff:fe5b:619d
- C. ff80:a9:8eec:4bff:fe5b:619d
- D. fe80::a9:8eec:4bff:fe5b:619d

Correct Answer: B

---

**QUESTION 4**

What is the function of the authentication service?

- A. Validates the user identity
- B. Determines switch management commands
- C. Validates switch order
- D. Determines which services the user is enabled to access

Correct Answer: A

---

**QUESTION 5**

What is the maximum number of LLDP neighbors supported per system with OS10?

- A. 250
- B. 256
- C. 384
- D. 512

Correct Answer: A

[DES-5221 PDF Dumps](#)

[DES-5221 Study Guide](#)

[DES-5221 Braindumps](#)