

# EX447<sup>Q&As</sup>

Red Hat Certified Specialist in Advanced Automation: Ansible Best Practices

## Pass RedHat EX447 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ex447.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by RedHat Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

**CORRECT TEXT**

Create a playbook that changes the default target on all nodes to multi-user.target. Do this in a playbook file called target.yml in /home/sandy/ansible

A. See the for complete Solution below.

Correct Answer: A

-

name: change default target

hosts: all

tasks:

-

name: change target

file:

src:/usr/lib/systemd/system/multi-user.target dest: /etc/systemd/system/default.target state:

link

---

**QUESTION 2**

**CORRECT TEXT**

Create a file called requirements.yml in /home/sandy/ansible/roles. A file called role.yml in /home/sandy/ansible/. The proxy-roles should be used on the proxy host. And when you curl http://node3.example.com it should display "Welcome to node4.example.com" and when you curl again "Welcome to node5.example.com" The php-roles should be used on the prod host.

A. See the for complete Solution below.

Correct Answer: A

Solution as:

```
- name: install haproxy and php roles
hosts: all
vars:
  haproxy_backend_servers:
    - name: web1
      address: node4.example.com
    - name: web2
      address: node5.example.com
tasks:
  - name: import haproxy
    include_role: haproxy-role
    when: "proxy" in group_names
  - name: import php
    include_role: php-role
    when: "prod" in group_names
```

Check the proxy host by `curlhttp://node3.example.com`

### QUESTION 3

#### CORRECT TEXT

Using the Simulation Program, perform the following tasks:

1.

Use an ansible ad-hoc command, check the connectivity of your servers.

2.

Use an ad-hoc ansible command, find the free space of your servers.

3.

Use an ad-hoc ansible command, find out the memory usage of your servers.

4.

Do an `ls -l` on the targets `/var/log/messages` file.

5.

Tail the contents of the targets `/var/log/messages` file.

A. See the for complete Solution below.

Correct Answer: A

1.

```
ansible all -m ping
```

2.

```
ansible all -a "/bin/df -h"
```

3.

```
ansible all-a "/usr/bin/free"
```

4.

```
ansible all -a "ls -l /var/log/messages"
```

5.

```
ansible local -b -a "tail /var/log/messages"
```

---

#### QUESTION 4

##### CORRECT TEXT

Create an empty encrypted file called myvault.yml in /home/sandy/ansible and set the password to notsafepw. Rekey the password to iwej2221.

A. See the for complete Solution below.

Correct Answer: A

```
ansible-vault create myvault.yml Create new password: notsafepw Confirm password: notsafepw ansible-vault rekey myvault.yml Current password: notsafepw New password: iwej2221 Confirm password: iwej2221
```

---

#### QUESTION 5

CORRECT TEXT Create an ansible vault password file called lock.yml with the password reallysafepw in the /home/sandy/ansible directory. In the lock.yml file define two variables. One is pw\_dev and the password is \\dev\\ and the other is pw\_mgr and the password is \\mgr\\ Create a regular file called secret.txt which contains the password for lock.yml.

A. See the for complete Solution below.

Correct Answer: A

```
ansible-vault create lock.yml New Vault Password: reallysafepw Confirm: reallysafepw
```

In file:

```
pw_dev: dev
pw_mgr: mgr
```

[Latest EX447 Dumps](#)

[EX447 Exam Questions](#)

[EX447 Braindumps](#)