

H12-711^{Q&As}

HCIA-Security V4.0

Pass Huawei H12-711 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h12-711.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Here on Client-Initialized the L2TP VPN, right there saying?(Choose three)

- A. L2TP tunnel connection request initiated remote users via PSTN / ISDN access to NAS, to get permission to access the Internet directly to the remote LNS.
- B. L2TP LNS device receives user connection requests,based on the user name and password to authenticate the user
- C. LNS assigns a private IP address for the remote user.
- D. VPN remote dial-up users do not need to install software

Correct Answer: ABC

QUESTION 2

The following types of firewall packet processing speed is the fastest non-first?

- A. Packet filtering firewall
- B. Proxy Firewall
- C. Stateful inspection firewall
- D. Software firewalls

Correct Answer: C

QUESTION 3

Which of the following does not support GRE technology?(Choose two)

- A. Tunneling
- B. Encryption and decryption technology
- C. Key management technology
- D. End checksum

Correct Answer: BC

QUESTION 4

Following the agreement,the work at the network layer have?(Choose two)

- A. ICMP

- B. IGMP
- C. FTP
- D. TELNET

Correct Answer: AB

QUESTION 5

L2TP VPN configuration on the following statement in the precautions are: (Choose three)

- A. The LNS L2TP client must be configured virtual interface template (Virtual-Template) the IP address of the virtual interface template needs to join the domain
- B. The default firewall requires authentication of the tunnel. If you do not configure authentication, you need to undo tunnel authentication command
- C. To enable L2TP dial-up users can normally access the network address, the address assigned to L2TP users can dial up the network and the user's address on the same network segment or need to enable proxy ARP
- D. LNS side is not allowed to configure multiple L2TP-Group

Correct Answer: ABC

[H12-711 PDF Dumps](#)

[H12-711 Exam Questions](#)

[H12-711 Braindumps](#)