

H12-811^{Q&As}

HCIA-Datacom V1.0

Pass Huawei H12-811 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h12-811.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

When using the ping command on the VRp platform, if you need to specify a P address as the source address of the echo request message, which of the following parameters should be used? ()

A. --d

B. --a

C. --S

D. --n

Correct Answer: B

QUESTION 2

The IPv6 protocol uses NS and NA. packets for duplicate address detection ().

A. True

B. False

Correct Answer: A

QUESTION 3

When adopting LACP mode for link aggregation, what is the default system interference level of Huawei switches? ()

A. 36864

B. 4096

C. 24576

D. 32768

Correct Answer: D

QUESTION 4

The load balancing modes at both ends of an Eth-Trunk can be different.

A. True

B. False

Correct Answer: A

QUESTION 5

OSPF Router ID must be the same as the IP address of an interface on the router.

A. True

B. False

Correct Answer: B

[H12-811 VCE Dumps](#)

[H12-811 Study Guide](#)

[H12-811 Exam Questions](#)