

H12-831^{Q&As}

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

Pass Huawei H12-831 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h12-831.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

CutoverThe previous information collection can be used to determine whether the services before and after the cutover are normal.

- A. right
- B. wrong

Correct Answer: A

QUESTION 2

IGP converges faster than BGP, which may cause network traffic loss. By enabling the OSPF and BGP linkage feature of the device, the device can keep the OSPF and BGP linkage during the set linkage time.____The router makes the link metric value in the LSA advertised to be the maximum value, so as to inform other OSPF devices not to use this router to forward data, so as to avoid traffic loss. (Note: If English letters are involved, all uppercase)

- A. STUB-ROUTER

Correct Answer: A

QUESTION 3

In an MPLS network, functions such as neighbor discovery, session establishment and maintenance, and label management are implemented by exchanging LDP messages between SRs running the DP protocol. To ensure the reliability of message delivery, all LDP messages are sent and received based on TCP connections.

- A. True
- B. False

Correct Answer: B

QUESTION 4

The IS-IS neighbor relationship between R3 and R1 is not established. According to the information in this figure, what is the possible reason?

```
Repeated System ID :0          Bad Circuit Type
Longer packet                More Area Addr
Longer Area Addr            Bad Area Addr TLV :0
More IF Addr                 Bad Formatted IF TLV
Mismatched Area Addr(LI): 0   Mismatched Proto
SNPA Conflicted (LAN): 0 .
```

- A. R3andR1ofIIHAuthentication failed
- B. R3andR1ofSystem IDrepeat
- C. R3andR1ofI5-LevelMismatch
- D. R3andR1the interconnect interfacecircuit-typeMismatchWhen troubleshooting MSTP faults, you executed the display current-configuration command to obtain

Correct Answer: C

QUESTION 5

Which of the following options is incorrect:

- A. Created by assigning labels staticallyLSPIt can also be dynamically adjusted according to changes in network topology, without administrator intervention.
- B. The principle to be followed when manually assigning labels is: the value of the outgoing label of the upstream node is the value of the incoming label of the downstream node
- C. LSPstaticLSPand dynamicLSPtwo kinds. staticLSPManual configuration by administrator, dynamicLSPthen use Dynamic establishment of label protocol
- D. dynamicLSPDynamically established through the label publishing protocol, such asMP- BGP, RSVP-TE, LDP

Correct Answer: C

[H12-831 Practice Test](#)

[H12-831 Study Guide](#)

[H12-831 Braindumps](#)