

H31-124_V2.0^{Q&As}

HCIP Carrier IP V2.0

Pass Huawei H31-124_V2.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/h31-124_v2-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which of the following are necessary for ISIS to support MPLS TE?

- A. Use command "traffic-eng" to enable ISIS-TE in IS-IS view.
- B. Use command "mpls-te enable" to enable MPLS TE in ISIS view.
- C. Use command "opaque-capability enable" to enable opaque capability in ISIS view.
- D. Configuring wide-metric support in ISIS view.

Correct Answer: AD

QUESTION 2

Which of the following statements about LAN switch is correct?

- A. LAN switch is transparent for user, it does not modify the data field of the forwarded frame.
- B. LAN switch can still operate normally even when loop exists.
- C. LAN switch can detect loop according to the contents of the packet.
- D. LAN switch can modify the data field of the forwarded frame when necessary.

Correct Answer: C

QUESTION 3

Which of the following multicast IP addresses is administratively scope address?

- A. 224.0.0.0-224.0.0.255
- B. 239.0.0.0-239.0.0.255
- C. 224.0.1.0-238.255.255.255
- D. 224.0.0.0-239.255.255.255

Correct Answer: D

QUESTION 4

Which of the following statements regarding the description of LDP is incorrect?

- A. Between two LSRs that run LDP, the LDP session is established and Label/FEC mapping information is exchanged.
- B. In MPLS, LDP is used to implement label distribution, label control and label retention.

- C. The two routers between which LDP session is established are called LDP Peer.
- D. The UDP and TCP port number for LDP is 64.

Correct Answer: ABC

QUESTION 5

Which of the following statements about CAR are correct?

- A. CAR uses token bucket mechanism to measure traffic and allocate bandwidth.
- B. CAR can be used for incoming interface and outgoing interface.
- C. CAR and queue scheduling cannot be used at the same time because of confliction.
- D. CAR can be used to limit the rate of the specific type of traffic.

Correct Answer: C

[Latest H31-124_V2.0 Dumps](#)

[H31-124_V2.0 PDF Dumps](#)

[H31-124_V2.0 Braindumps](#)