

# H31-124\_V2.0<sup>Q&As</sup>

HCIP Carrier IP V2.0

## Pass Huawei H31-124\_V2.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

[https://www.pass2lead.com/h31-124\\_v2-0.html](https://www.pass2lead.com/h31-124_v2-0.html)

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

If Adjacency Segment + Node Segment is used together, the entire path can be forced to include an adjacency and load balancing. This mode is called loose path.

- A. True
- B. False

Correct Answer: B

---

#### QUESTION 2

Which of the following access modes can be used by leaf nodes in a data center?

- A. Single-node system deployment
- B. ToR Deploying an SVF System
- C. Deploying the M-Lag on the ToR
- D. ToR Stack Deployment

Correct Answer: C

---

#### QUESTION 3

Which of the following statements about CAR are correct?

- A. CAR uses token bucket mechanism to measure traffic and allocate bandwidth.
- B. CAR can be used for incoming interface and outgoing interface.
- C. CAR and queue scheduling cannot be used at the same time because of confliction.
- D. CAR can be used to limit the rate of the specific type of traffic.

Correct Answer: C

---

#### QUESTION 4

Which of the following statement are correct regarding TTL value in VRRP packet?

- A. The VRRP packet is only forwarded in one IP network, so the TTL value is always set to 1.
- B. The TTL value of device from different manufactures is different; on VRRP, the TTL value is 1.
- C. By default, the VRRP packet with TTL value not equal to 255 will be dropped; On VRRP, we can use some commands to disable the function of detecting TTL value.

D. The TTL value must be 255 In normal VRRP packet.

Correct Answer: B

---

#### QUESTION 5

Which of the following statements regarding DIS election is correct?

- A. When the priority is the same, the router with higher IP address will be elected as the DIS.
- B. When a DIS fails, the backup DIS will take over.
- C. The IS-IS router with the highest priority in the whole broadcast network will be elected as the DIS.
- D. DIS election is configured manually.

Correct Answer: ABC

[H31-124 V2.0 Practice Test](#) [H31-124 V2.0 Study Guide](#) [H31-124 V2.0 Braindumps](#)