

# H31-611<sup>Q&As</sup>

HCNA - SDN(Huawei Certified Network Associate - SDN)

## Pass Huawei H31-611 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h31-611.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

For a router that runs BGP4, which of the following statements is not true?

- A. When multiple paths exist, BGP4 selects the optimal path.
- B. BGP notifies the routes obtained from EBGP to all its BGP peers.
- C. BGP advertises to BGP peers only the routes it uses.
- D. BGP4 notifies the routes obtained from IBGP to all its BGP peers.

Correct Answer: B

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1100028526?section=j06yandtopicName=configuring-bgp4-load-balancing>

---

#### QUESTION 2

The OpenStack architecture comprises which of the following components? (Choose all that apply.)

- A. Nova
- B. Neutron
- C. Cinder
- D. NetMatrix

Correct Answer: ABC

---

#### QUESTION 3

What kind of packet is used by BGP to transmit version number and AS number information?

- A. Open
- B. Update
- C. Keepalive
- D. Notification

Correct Answer: A

Reference: <http://www.ciscopress.com/articles/article.asp?p=2756480andseqNum=3>

---

#### QUESTION 4

Which of the following statements is true about the IS-IS backbone area?

- A. A router belongs to all areas.
- B. All routers belong to the same area.
- C. This area comprises a series of continuous L2 routers and L1-L2 routers.
- D. This area is central area connected to other areas.

Correct Answer: C

Reference: <https://www.sciencedirect.com/topics/computer-science/internal-router>

---

#### QUESTION 5

Which of the following statements is true about proxy ARP?

- A. Proxy ARP allows a gateway directly connected to the host to use its own MAC address to reply to ARP requests in place of destination host.
- B. Proxy ARP allows a gateway directly connected to the host to help the destination host to transmit ARP packets across VLANs.
- C. Proxy ARP is used for communication within a VLAN.
- D. Proxy ARP means to buy the permission to use ARP packets from a proxy.

Correct Answer: A

Reference: <https://support.huawei.com/enterprise/en/doc/EDOC1000166635/620f63f3/proxy-arp>

[H31-611 VCE Dumps](#)

[H31-611 Study Guide](#)

[H31-611 Exam Questions](#)