

H35-211^{Q&As}

HCIP-Access V2.5

Pass Huawei H35-211 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h35-211.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

(single) MA5600T/MA5680T When performing FTTH service and data planning, which of the following parameters cannot be duplicated under the same PON port?

- A. TCONT-ID
- B. CVLAN ID
- C. SVLAN ID
- D. ONT ID

Correct Answer: D

QUESTION 2

(Radio) Regarding multicast, the following description is incorrect

- A. Add Lgmp user under BTV, and by default, multicast users can watch 8 programs.
- B. The user-issued Report is captured in the single board logic and sent to the single board CPU
- C. Device-based global configurations of Layer 2 groups refer to common parameters of protocols (IGMP Proxy, GMP Snoop) to all
- D. When the igmp match mode disables, you need to configure the multicast program group

Correct Answer: D

QUESTION 3

(single) Which of the following network topologies is the most secure topology?

- A. Ring structure
- B. Chain structure
- C. Star structure
- D. Full mesh structure

Correct Answer: D

QUESTION 4

(Radio) A power access service deploys GPON Type C dual attribution protection, and the protection group is fixed with the upstream Ethernet port status on the OLT, and when the Ethernet port status associated with the protection group on the OLT becomes down, the following description is incorrect.

- A. The state of the onU side work port changes to standby
- B. OLT laughs at onu uplink state changes
- C. After the inversion, the service on the ONU is sent to the OLT through the protect port, that is, the service packet is transmitted on the protect example planting road
- D. The ONU detects link failures and triggers protection reversals

Correct Answer: D

QUESTION 5

(multiple) What content do I need to configure when adding ont-linepmfile as a template on the MA5600T/ MA5680T?

- A. Configure the vlan of the ONT ETH port.
- B. Add DBA template
- C. Binding tcont and DBA templates
- D. Increase gempport and configure gempport mapping

Correct Answer: CD

[H35-211 Practice Test](#)

[H35-211 Study Guide](#)

[H35-211 Exam Questions](#)