

HCE-3700^{Q&As}

Hitachi Vantara Certified Expert - Performance architect

Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hce-3700.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which three statements are true regarding the Hitachi external storage architecture? (Choose three.)

- A. Enabling Cache Mode increases exposure to problems with high Cache Write Pending.
- B. Enabling Cache Mode allows destaging asynchronously from host I/O.
- C. Enabling Cache Mode always improves performance.
- D. A System Option mode can force in sequence destaging even when destaging asynchronously.
- E. Disabling Cache Mode for an external LDEV eliminates the use of cache.

Correct Answer: ABD

QUESTION 2

What are two appropriate criteria for evaluating a batch job performance? (Choose two.)

- A. elapsed time and/or throughput (MBs, IOPS)
- B. storage response time
- C. customer requirements
- D. host initiators utilization

Correct Answer: AB

QUESTION 3

You are planning for a performance upgrade for a transaction application.

Which three metrics are necessary to determine the required back-end storage configuration in this scenario? (Choose three.)

- A. cache read hit ratio
- B. read/write ratio
- C. transfer rates
- D. queue depth
- E. IOPS

Correct Answer: ABE

QUESTION 4

What are two benefits of placing transaction log files on RAID 1+0 disks for Microsoft SQL Server databases rather than RAID 5 disks? (Choose two.)

- A. Multiple transaction log files are supported.
- B. Faster recovery after disk hardware failure is realized.
- C. Capacity utilization rates are improved.
- D. Microsoft recommendations are followed.

Correct Answer: AB

QUESTION 5

Relocation cycles are regulatory failing to complete in an HDT implementation where the customer is also reporting lower than expected performance.

What should be done in this scenario?

- A. Change to Continuous mode and increase the monitor period cycle time.
- B. Change to Period mode and increase the monitor period cycle time.
- C. Change to Period mode and reduce the monitor period cycle time.
- D. Change to High-Performance mode and reduce the monitor period cycle time.

Correct Answer: B

[HCE-3700 PDF Dumps](#)

[HCE-3700 Practice Test](#)

[HCE-3700 Braindumps](#)