

HP0-Y50^{Q&As}

Architecting HP FlexNetwork Solutions

Pass HP HP0-Y50 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-y50.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A network architect has designed a two-tier topology for the campus LAN and is planning to implement routing at the core. Which requirement might cause the network architect to consider implementing routing at the access layer?

- A. Employees in different VLANs need to use collaboration applications to share high-resolution graphic files
- B. The solution must support an isolated VLAN for wired guest devices
- C. Employees need to be placed in dynamic VLANs, assigned by a RADIUS server in identity, so that network managers can manage the solution more easily
- D. The customer has an HP Unified Wired-WLAN solution, and wireless users need to roam seamlessly across the site

Correct Answer: A

QUESTION 2

After analyzing a hospital's applications, the network architect identifies two life-critical applications. What is the availability requirement for a life-critical application?

- A. 99%
- B. 99.9%
- C. 99.99%
- D. 99.999%

Correct Answer: D

QUESTION 3

A network architect is designing a redundancy solution for a customer and has learned that there is a single link between two critical network components. During the past 4000 hours of operation, the link has failed twice. The customer estimates that each failure has taken two hours to resolve.

Given this information, what is the availability that this link currently provides?

- A. Less than 99.99%
- B. 99.9%
- C. 99.99%
- D. 99.999%

Correct Answer: B

QUESTION 4

A customer requires high availability for wireless services at branches. The customer also wants to centralize management and traffic distribution as much as possible. What should the architect suggest?

- A. Controlling branch APs with one or more HP 7500/10500 20G Wired-WLAN at the main office and enabling remote-AP features
- B. Controlling branch APs with a cluster of HP 830 Unified Wired-WLAN switches, one of which is deployed at the main office and one of which is deployed at the branch
- C. Deploying the APs without a controller but managing them with HP Intelligent Management Center (IMC) Wireless Services Manager (WSM)
- D. Controlling Branch APs with two HP 830 Unified Wired-WLAN switches, which are deployed at the main office

Correct Answer: D

QUESTION 5

A network architect is planning a complete access layer and core upgrade for customer's campus LAN. The campus has four large buildings, each requiring between 1000 and 3000 edge ports. Which factor will play a primary role in determining whether the network architect needs to plan a two-tier or three-tier topology for the campus LAN?

- A. The number of fiber links between each building and the building where the core switches reside
- B. Whether the customer requires a wireless solution
- C. The high number of edge ports that the solution requires
- D. Whether the customer can afford core switches that support intelligent Resilient Framework (IRF)

Correct Answer: C

[Latest HP0-Y50 Dumps](#)

[HP0-Y50 VCE Dumps](#)

[HP0-Y50 Practice Test](#)