

# HP0-Y52<sup>Q&As</sup>

Applying HP FlexNetwork Fundamentals

**Pass HP HP0-Y52 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-y52.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

What is one feature that MSTP has that RSTP does not have?

- A. load-sharing on redundant links
- B. alternate root ports
- C. multiple designated ports per segment
- D. one set of BPDUs per VLAN

Correct Answer: A

---

#### QUESTION 2

Which HP software platform provides centralized network management, monitoring, and configuration of wired and wireless network infrastructure devices, as well as traffic monitoring, user management, and other capabilities?

- A. HP IntelligentManagement Center (IMC)
- B. HP Intelligent Resilient Framework (IRF)
- C. HP Virtual Cloud Networking (VCN)
- D. HP Virtual Connect FlexFabric

Correct Answer: A

---

#### QUESTION 3

A customer is implementing an access layer solution with four HP Comware switches in an Intelligent Resilient Framework (IRF) virtual device or domain. The customer expects to add two additional switches of the same model and would like to add them to the existing IRF virtual device. What must the customer verify?

- A. that the IRF virtual device has spanning tree enabled on it
- B. that the new switches are both assigned the same member ID as the master of the existing IRF virtual device
- C. that the IRF virtual device is using a daisy chain topology to provide better resilience
- D. that the switch model supports at least six switches in an IRF virtual device

Correct Answer: A

---

#### QUESTION 4

A company has a policy that requires all administrators to use secure access for in-band management. The administrator sets up SSH access on the HP Comware switches in the network to meet this requirement. The

administrator enables SSH, and creates SSH keys and administrator accounts on the Comware switches. Every time the administrator attempts to log in to the switches the SSH access is denied. The VTYs are configured as: user-interface vty 0 15 authentication-mode password user privilege level 3 quit What is the correct authentication mode the administrator must configure on the VTYs of the Comware switch so the switch prompts for usernames and passwords?

- A. username
- B. aaa
- C. scheme
- D. local

Correct Answer: C

### QUESTION 5

Refer to the exhibit.

```
Provision-1(config)# show spanning-tree 1,19,21 instance ist
<-output omitted->
```

Port	Type	Cost	Priority	Role	State	Designated Bridge
1	100/1000T	20000	128	Designated	Forwarding	d4c9ef-851680
19	100/1000T	20000	128	Root	Forwarding	d07e28-cec94f
21	100/1000T	20000	128	Alternate	Blocking	d07e28-ced31e

This switch currently assigns all VLANs to Multiple Spanning Tree Protocol (MSTP) instance 0 or the Internal Spanning Tree (IST). Which statement correctly describes interface 21?

- A. The interface is down at Layer 2; it is not available for sending or receiving any traffic.
- B. The interface is an edge port but has received Bridge Protocol Data Units (BPDUs), so it is disabled.
- C. The interface does not forward or accept data traffic, but it is ready to start forwarding if interface 19 fails.
- D. The interface does not support spanning tree; it is possible that it will introduce a loop in the network.

Correct Answer: C