

HP2-Z32^{Q&As}

Implementing HP MSM Wireless Networks

Pass HP HP2-Z32 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp2-z32.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A company is deploying an HP MSM760 Controller that will control approximately 80 HP MSM APs. The HP MSM solution will provide wireless guest services and a WLAN for employees, which is secured with WPA2 and 802.1X.

The controller will perform the following functions: Handle all guest traffic

Provide DHCP services for guest clients

Force guests to log in through a web page and implement access controls

How should the network administrator connect the controller to the corporate LAN?

- A. The administrator must connect both the LAN port and the Internet port, and the ports must be in different VLANs.
- B. The administrator can connect either the LAN port or the Internet port, or both ports, but it is typically recommended to connect the Internet port.
- C. The administrator must connect both the LAN port and the Internet port, and the ports must be in the same VLAN.
- D. The administrator must connect only the LAN port.

Correct Answer: D

QUESTION 2

A company needs a WLAN for its employees. Network administrators are planning a non-access-controlled VSC that enforces WPA2 and 802.1x. The network administrators want to assign wireless clients to VLAN 10 in building 1 and to VLAN 20 in building 2.

What is the proper design?

- A. Two VSCs each of which specifies a different egress VLAN
- B. One VSC that specifies two egress VLANs
- C. Two VSCs each of which specifies a different ingress VLAN
- D. One VSC that is bound to two AP groups using different egress VLANs

Correct Answer: D

QUESTION 3

A company wants to use MSM765 zJ Controllers in a team solution that supports 750 MSM APs. What must the company purchase for this solution?

- A. Six MSM765 zJ Controllers
- B. Five MSM765 zJ Controllers and an additional Premium license for each one

- C. Four MSM765 zl Controllers and an additional Premium license for each one
- D. Four MSU765 zl Controllers

Correct Answer: B

QUESTION 4

You have decided to limit access to the management GUI to clients on your local network. This requires you to select which item from Active interfaces on your Management screen?

- A. VPN
- B. LAN port
- C. Internet port
- D. VLAN/GRE item

Correct Answer: B

QUESTION 5

A company has an MSM720 Controller and wants to implement a team solution. What is the guideline for implementing teaming with MSM720 Controllers?

- A. The team can include a maximum of five members, which must have a Premium license.
- B. The team can include a maximum of five members, which must have a Mobility license.
- C. The team can include a maximum of two members, which must both have a Premium Mobility license.
- D. The team can include a maximum of three members, which must have a Teaming license.

Correct Answer: C

[Latest HP2-Z32 Dumps](#)

[HP2-Z32 Exam Questions](#)

[HP2-Z32 Braindumps](#)