

HP2-Z33^{Q&As}

HP Unified Wired-Wireless Networks and BYOD

Pass HP HP2-Z33 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp2-z33.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A network administrator configures an HP BYOD solution. To authorize guests to register their endpoints, the network administrator sets up components of the Onboarding process. Which configuration settings must the administrator set up in User Access Manager?

- A Guest Account
BYODAnonymous Access Service
- B Default BYOD User
BYODAnonymous Access Condition
- C Guest Account
BYODAnonymous Access Condition
- D Default BYOD User
BYODAnonymous Access Service

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: D

QUESTION 2

A customer has an HP BYOD solution based on an HP 830 Unified Wired-Wireless Controller and HP 425 Access Points (APs). To ease the controller adoption of the APs, a VLAN is set up on the corporate LAN. How should this VLAN be configured?

- A. Set the VLAN on the switches between the APs and Comware L3 switch
- B. Set the VLAN as VLAN 1
- C. Set the VLAN on the switches between the APs and 830 wireless controller
- D. Set the VLAN on the switches between the APs and the 830 switch

Correct Answer: A

QUESTION 3

A network administrator sets up the DHCP relay on an HP Comware Layer 3 device that forwards IP traffic between the VLANs associated with the wireless SSID with these commands.

```
interface Vlan-interface 100
description internet access
ip address 10.1.100.1 255.255.255.0
dhcp select relay
dhcp relay server-select 0
```

What must the administrator configure prior to enabling the DHCP relay to the DHCP server on 10.0.0.200 in the interface vlan-interface 100?

- A Interface vlan 100
dhcp relay server-group 0 ip 10.0.0.200
- B system-view
dhcp enable
dhcp relay server-group 0 ip 10.0.0.200
- C system-view
dhcp select relay
dhcp relay server-group 0 ip 10.0.0.200
- D system-view
dhcp relay server-group 0 ip 10.0.0.200

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

QUESTION 4

When does DHCP fingerprinting of endpoints occur within an HP BYOD solution?

A. when User Access Manager validates the user account

B. when endpoints access the BYOD registration page

C. when endpoints obtain an IP address

D. when endpoints are authenticated

Correct Answer: C

QUESTION 5

Which statement is correct about security on a wireless network?

- A. 802.1X with EAP-TLS mode provides encryption without authentication.
- B. In MAC authentication, the MAC address can be spoofed.
- C. 802.1X with PEAP MSCHAPV2 provides authentication without encryption.
- D. MAC authentication provides encryption.

Correct Answer: B

[HP2-Z33 PDF Dumps](#)

[HP2-Z33 Practice Test](#)

[HP2-Z33 Study Guide](#)