

# HPE0-J80<sup>Q&As</sup>

Delta - Architecting Multi-Site HPE Storage Solutions

**Pass HP HPE0-J80 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hpe0-j80.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which information should be collected and analyzed when discovering customer expectations for replication performance? (Select two.)

- A. rate of data change
- B. bandwidth
- C. type of data
- D. latency
- E. frequency of copies

Correct Answer: AD

---

**QUESTION 2**

A customer purchased an HPE 3PAR all-flash array to accelerate the company's databases. The customer is concerned about the risk of data loss. Synchronous replication is currently being used, but it is causing slow I/O due to limited network bandwidth and latency, both of which cause application slowdown.

Which alternative solution should you propose to address the issue?

- A. Asynchronous Streaming Remote Copy
- B. Synchronous Long Distance Remote Copy
- C. Periodic Asynchronous Remote Copy
- D. Peer Persistence

Correct Answer: C

---

**QUESTION 3**

You are designing a Fibre Channel storage solution for a customer who is currently attaching all hosts through the Ethernet and the TCP/IP protocol.

What is an advantage of choosing Fibre Channel over TCP/IP?

- A. Less costly networking hardware
- B. Support for greater distances
- C. Less overhead
- D. More robust error correction

Correct Answer: D

---

#### QUESTION 4

You are designing an iSCSI solution for a customer with one data center, who is investing in a second data center that will be ready in the near future. The networking infrastructure of the current data center is generally sufficient for use with an iSCSI storage solution, but it is from a different vendor. The new data center will be equipped with current HPE Networking switches.

- A. For maximum performance, Jumbo Frames should be configured on the storage nodes only
- B. Jumbo Frames are only required for low latency applications
- C. Jumbo Frame sizes are not standardized across all switch vendors
- D. Only switch ports must be configured to forward Jumbo Frames

Correct Answer: C

---

#### QUESTION 5

A customer has almost reached the maximum number of domain IDs in a B-series, Fibre Channel SAN fabric. The company has also recently acquired another company and needs to integrate their C-series Fibre Channel SAN to be able to share the SAN infrastructure.

Which feature should you enable on the C-series, Fibre Channel edge switches to meet these requirements?

- A. NPV mode
- B. FSPF routing
- C. hard zoning
- D. soft zoning

Correct Answer: C

[HPE0-J80 PDF Dumps](#)

[HPE0-J80 VCE Dumps](#)

[HPE0-J80 Study Guide](#)