

HPE0-S55^{Q&As}

Delta - Designing HPE Server Solutions

Pass HP HPE0-S55 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hpe0-s55.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A c7000 customer wants to expand their server environment. You want to encourage them to move synergy to prepare them for the future.

Which question should you ask?

- A. Is there a requirement for enhanced security on the management network?
- B. Do they want to maximize the memory footprint of their server?
- C. Does their application workload benefit from persistence memory?
- D. Are they planning to purchase proLiant Gen 10 server as part of the project?

Correct Answer: D

QUESTION 2

A customer needs a VDI solution. The amount of computer per U OF rack space will be key point in their final solution selection.

Which HPE product would be an ideal solution as part of your RFP response?

- A. HPE Apollo 4510 gen10
- B. HPE Apollo 4200 Gen9
- C. HPE SY480 Gen 10
- D. HPE DL580 Gen10

Correct Answer: A

QUESTION 3

You customer has completed a successful proof of Concept (PoC) consisting of a single frame with dual composers and virtual Connect SE 40GB F8 modules. The customer wants to: *add a second frame before they move into production *have unified management *have separate logical enclosure for each frame

What are basic steps to add the second frame?

- A. Move the standby composer to the second frame
- B. Disconnect the existing management ring, and then cable the FLM (frame link module) in the first frame to the FLMs in the second frame
- C. install a satellite module in the first frame

- D. Move the bottom VC module from the first frame to the second
- E. Move one of the uplinks from the FLM in the first frame to a FLM in the second

Correct Answer: E

QUESTION 4

While installing a three frame Synergy solution, only two of the frames are identified during the discovery process.

What should you do to get resolution?

- A. Remove and re-insert the standby Composer.
- B. Issue a refresh command to the enclosure.
- C. Open the front panel Composer, and read the error message.
- D. Validate Frame link Module topology.

Correct Answer: D

QUESTION 5

A customer has a ProLiant DL based Gen10 server solution hosting an I/O intensive 2TB database. The customer needs to dramatically increase the performance of their existing system.

- A. Install HPE Scalable persistence Memory
- B. Move the OS to an M2 SSO drive
- C. Update the current processor to a Xeon-platinum
- D. Install DO4 Smart Memory

Correct Answer: A

[Latest HPE0-S55 Dumps](#)

[HPE0-S55 Practice Test](#)

[HPE0-S55 Braindumps](#)