

HPE6-A42^{Q&As}

Implementing Aruba WLAN (IAW) 8

Pass HP HPE6-A42 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hpe6-a42.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.

Exam_Employee	General	VLANs	Security	Access
Name (ssid):	Exam_Employee			
Primary usage:	<input checked="" type="radio"/> Employee <input type="radio"/> Guest			
	Select AP Groups <input type="button" value="v"/>			
Broadcast on:	<input checked="" type="checkbox"/> default <input type="checkbox"/> Public Areas <input type="button" value="▲"/> <input type="button" value="▼"/>			
Forwarding mode:	Tunnel <input type="button" value="v"/>			
Broadcast SSID:	No <input type="button" value="v"/>			

What describes the behavior for this WLAN?

- A. APs in the default group broadcast the SSID. Clients can connect to the WLAN on APs in the default group only.
- B. No APs broadcast the SSID. Clients cannot connect to the WLAN until administrators activate it.
- C. No APs broadcast the SSID. Clients can connect to the WLAN on APs in the default group only.
- D. APs in the default group broadcast the SSID. Clients can connect to the WLAN on APs in any group.

Correct Answer: C

QUESTION 2

A company has a single Aruba Mobility Master (MM)-based solution with two Mobility Controllers (MCs). Network administrators want APs in building 1 to support a WLAN but do not want APs in building 2 to support the WLAN.

How can administrator ensure that they can enforce this rule as they set up the WLAN in the Mobility Master (MM) Interface?

- A. Place APs in different buildings in different AP Groups.

- B. Assign APs in different buildings to different MM nodes.
- C. Configure APs in different buildings to use different frequency bands.
- D. Assign different radio profiles to APs in different buildings.

Correct Answer: A

QUESTION 3

An Aruba solution runs ArubaOS 8 and uses a standalone controller architecture. Which feature can administrators use to optimize the channel and power plan for the APs?

- A. ARM
- B. Rule Based Client Match
- C. AirMatch
- D. AppRF

Correct Answer: A

QUESTION 4

A network administrator monitors an Aruba Mobility Controller with Aruba AirWave and sees the configuration status is Error. What should the administrator conclude?

- A. AirWave checks the controller configuration and detects a syntax error.
- B. AirWave determines that the controller configuration does not match the template for its group.
- C. AirWave has a communication issue with the controller and cannot check the configuration.
- D. AirWave detects a mismatch with the controller configuration and software version.

Correct Answer: C

QUESTION 5

Which task can an Aruba Air Monitor (AM) perform?

- A. Analyze wireless traffic patterns at the application level.
- B. Optimize RF through the AP channel and transmit power plans.
- C. Analyze RF signals to determine the cause of non-802.11 interference.
- D. Help to detect rogue APs in the environment.

Correct Answer: D

[Latest HPE6-A42 Dumps](#)

[HPE6-A42 PDF Dumps](#)

[HPE6-A42 Practice Test](#)