

# JN0-349<sup>Q&As</sup>

Enterprise Routing and Switching - Specialist (JNCIS-ENT)

## Pass Juniper JN0-349 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-349.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Click the Exhibit button.

```
user@host# show interfaces
ge-0/0/0 {
    unit 0{
        family iso;
        family inet {
            address 10.0.24.1/24;
        }
    }
}
ge-0/0/1 {
    unit 0{
        family iso;
        family inet {
            address 10.0.25.1./24;
        }
    }
}
ge-0/0/2 {
    unit 0{
        family iso;
        family inet {
            address 10.0.26.1/24;
        }
    }
}
lo {
    unit 0{
        family inet {
            address 192.168.2.1/32;
        }
    }
}
user@host#show protocols isis
interface ge-0/0/0.0 {
    level 1 disable;
}
interface ge-0/0/1.0 {
    level 2 disable;
}
interface ge-0/0/2.0 {
    level 2 disable;
}
interface lo0 {
    level 2 disable;
}
}
```

You are attempting to set up IS-IS on a device that has two interfaces (ge-0/0/1.0 and ge-0/0/2.0) in Level 1 and one interface (ge-0/0/0.0) in Level 2; however, it does not participate in either level.

Referring to the exhibit, what is the problem?

- A. The ge-0/0/0.0 interface must have the Level 1 disable statement removed.
- B. The lo0 interface must participate in both levels. . One of the interfaces requires a network entity title on it.
- C. All of the interfaces must have the level disable statement removed.

Correct Answer: C

---

### QUESTION 2

Which three statements describe what happens when processing a frame for a switched packet? (Choose three.)

- A. The ingress PFE performs the MAC address lookup.
- B. The frame enters the ingress port and is forwarded out all ports.
- C. The frame enters the ingress port and is processed by the ingress PFE.
- D. The ingress PFE sends the header information to the Routing Engine.
- E. The egress PFE forwards the packet out the egress port towards the destination.

Correct Answer: ACE

---

### QUESTION 3

What is the default route preference for BGP?

- A. 150
- B. 167
- C. 170
- D. 179

Correct Answer: C

---

### QUESTION 4

Your BGP router receives routes from two upstream ISPs: ISP A and ISP B. In this scenario, which change would you make to prefer routes from ISP A?

- A. Set the local-preference attribute for all routes received from ISP A to 200 while all routes received from ISP B use the default local-preference value of 100.

- B. Prepend the AS path to all routes received from ISP A while all routes received from ISP B use the default AS path value.
- C. Change the MED value for all routes received from ISP A to 1 while all routes from ISP B remain configured with no MED value.
- D. Set the local-preference attribute for all routes received from ISP A to 50 while all routes received from ISP B use the default local-preference value of 100.

Correct Answer: A

---

#### QUESTION 5

Which two statements are true about a unified in-service software upgrade (ISSU)? (Choose two.)

- A. The graceful Routing Engine switchover (GRES) and nonstop active routing (NSR) features must be enabled.
- B. It is possible to take PICs offline or bring them online during a unified ISSU.
- C. Unified ISSU is only supported by the dual Routing Engine platforms.
- D. The master Routing Engine and backup Routing Engine can be running different Junos versions before performing a unified ISSU.

Correct Answer: AC

[Latest JN0-349 Dumps](#)

[JN0-349 Practice Test](#)

[JN0-349 Exam Questions](#)