

# JN0-636<sup>Q&As</sup>

Service Provider Routing and Switching Professional (JNCIP-SP)

## Pass Juniper JN0-636 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-636.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

Exhibit

```
user@router> show security flow session
Session ID: 36, Policy name: pre-id-default-policy/n, Timeout: 2, Valid
  In: 10.10.10.2/61606 --> 203.0.113.100/179;tcp, Conn Tag: 0x0, If: ge-0/0/2.0,
Pkts: 1, Bytes: 64,
  Out: 203.0.113.100/179 --> 203.0.113.1/61606;tcp, Conn Tag: 0x0, If:
.local..0, Pkts: 1, Bytes: 40,
```

Referring to the exhibit, which type of NAT is being performed?

- A. Static NAT
- B. Destination NAT
- C. Persistent NAT
- D. Source NAT

Correct Answer: D

---

### QUESTION 2

Exhibit

```
Aug 3 01:28:23 01:28:23.434801:CID-0:THREAD_ID-01:RT: <172.20.101.10/59009-
>10.0.1.129/22;6,0x0> matched filter MatchTraffic:
Aug 3 01:28:23 01:28:23.434805:CID-0:THREAD_ID-01:RT: packet [64] ipid =
36644, @0xef3edece
Aug 3 01:28:23 01:28:23.434810:CID-0:THREAD_ID-01:RT: ---- flow_process_pkt:
(thd 1): flow_ctxt type 15, common flag 0x0, mbuf 0x6918b800, rtbl_idx = 0
Aug 3 01:28:23 01:28:23.434817:CID-0:THREAD_ID-01:RT: ge-
0/0/4.0:172.20.101.10/59009->10.0.1.129/22, tcp, flag 2 syn
Aug 3 01:28:23 01:28:23.434819:CID-0:THREAD_ID-01:RT: find flow: table
0x206a60a0, hash 43106(0xffff), sa 172.20.101.10, da 10.0.1.129, sp 59009, dp
22, proto 6, tok 9, conn-tag 0x00000000
Aug 3 01:28:23 01:28:23.434822:CID-0:THREAD_ID-01:RT: no session found,
start first path. in_tunnel - 0x0, from_cp_flag - 0
Aug 3 01:28:23 01:28:23.434826:CID-0:THREAD_ID-01:RT:
flow_first_create_session
Aug 3 01:28:23 01:28:23.434834:CID-0:THREAD_ID-01:RT: flow_first_in_dst_nat:
in <ge-0/0/3.0>, out <N/A> dst_adr 10.0.1.129, sp 59009, dp 22
Aug 3 01:28:23 01:28:23.434835:CID-0:THREAD_ID-01:RT: chose interface ge-
0/0/4.0 as incoming nat if.
Aug 3 01:28:23 01:28:23.434838:CID-0:THREAD_ID-01:RT:
flow_first_rule_dst_xlate: DST no-xlate: 0.0.0.0(0) to 10.0.1.129(22)
Aug 3 01:28:23 01:28:23.434849:CID-0:THREAD_ID-01:RT: flow_first_routing:
vr_id 0, call flow_route_lookup(): src_ip 172.20.101.10, x_dst_ip 10.0.1.129,
in ifp ge-0/0/4.0, out ifp N/A sp 59009, dp 22, ip_proto 6, tos 0
Aug 3 01:28:23 01:28:23.434861:CID-0:THREAD_ID-01:RT: routed (x_dst_ip
10.1.0.129) from trust (ge-0/0/4.0 in 0) to ge-0/0/2.0, Next-hop: 10.0.1.129
Aug 3 01:28:23 01:28:23.434863:CID-0:THREAD_ID-01:RT:
flow_first_policy_search: policy search from zone trust-> zone untrust
(0x0,0xe6810016,0x16)
Aug 3 01:28:26 01:28:26.434137:CID-0:THREAD_ID-01:RT: packet dropped, denied
by policy
Aug 3 01:28:26 01:28:26.434137:CID-0:THREAD_ID-01:RT: denied by policy Deny-
Telnet(5), dropping pkt
Aug 3 01:28:26 01:28:26.434138:CID-0:THREAD_ID-01:RT: packet dropped,
policy deny.
```

Referring to the exhibit, which statement is true?

- A. This custom block list feed will be used before the Juniper SecIntel
- B. This custom block list feed cannot be saved if the Juniper SecIntel block list feed is configured.
- C. This custom block list feed will be used instead of the Juniper SecIntel block list feed
- D. This custom block list feed will be used after the Juniper SecIntel block list feed.

Correct Answer: D

### QUESTION 3

What are two valid modes for the Juniper ATP Appliance? (Choose two.)

- A. flow collector

- B. event collector
- C. all-in-one
- D. core

Correct Answer: AC

Explanation: The Juniper ATP Appliance supports two valid modes of operation:

Flow Collector: This mode allows the Juniper ATP Appliance to collect and analyze network flow data to detect malicious activity.

All-in-One: This mode allows the Juniper ATP Appliance to perform both flow collection and event collection. It includes all the features of the Flow Collector and Event Collector mode.

Event collector and core are not valid modes for the Juniper ATP Appliance, the first one is focused on collecting events and the second one is a term that's not related to the appliance.

---

#### QUESTION 4

You want to identify potential threats within SSL-encrypted sessions without requiring SSL proxy to decrypt the session contents. Which security feature achieves this objective?

- A. infected host feeds
- B. encrypted traffic insights
- C. DNS security
- D. Secure Web Proxy

Correct Answer: C

---

#### QUESTION 5

Exhibit

```
Aug  3 01:28:23 01:28:23.434801:CID-0:THREAD_ID-01:RT: <172.20.201.10/59009->10.0.1.129/22;6,0x0> matched filter MatchTraffic:
Aug  3 01:28:23 01:28:23.434805:CID-0:THREAD_ID-01:RT: packet [64] ipid = 36644, @0xef3edece
Aug  3 01:28:23 01:28:23.434810:CID-0:THREAD_ID-01:RT: ---- flow_process_pkt: (thd 1): flow_ctxt type 15, common flag 0x0, mbuf 0x6918b800, rtbl_idx = 0
Aug  3 01:28:23 01:28:23.434817:CID-0:THREAD_ID-01:RT: ge-0/0/4.0:172.20.101.10/59009->10.0.1.129/22, tcp, flag 2 syn
Aug  3 01:28:23 01:28:23.434819:CID-0:THREAD_ID-01:RT: find flow: table 0x206a60a0, hash 43106(0xffff), sa 172.20.101.10, da 10.0.1.129, sp 59009, dp 22, proto 6, tok 9, conn-tag 0x00000000
Aug  3 01:28:23 01:28:23.434822:CID-0:THREAD_ID-01:RT: no session found, start first path. in_tunnel - 0x0, from_cp_flag - 0
Aug  3 01:28:23 01:28:23.434826:CID-0:THREAD_ID-01:RT:
  flow_first_create_session
Aug  3 01:28:23 01:28:23.434834:CID-0:THREAD_ID-01:RT: flow_first_in_dst_nat: in <ge-0/0/3.0>, out <N/A> dst_adr 10.0.1.129, sp 59009, dp 22
Aug  3 01:28:23 01:28:23.434835:CID-0:THREAD_ID-01:RT: chose interface ge-0/0/4.0 as incoming nat if.
Aug  3 01:28:23 01:28:23.434838:CID-0:THREAD_ID-01:RT:
  flow_first_rule_dst_xlate: DST no-xlate: 0.0.0.0(0) to 10.0.1.129(22)
Aug  3 01:28:23 01:28:23.434849:CID-0:THREAD_ID-01:RT: flow_first_routing: vr_id 0, call flow_route_lookup(): src_ip 172.20.101.10, x_dst_ip 10.0.1.129, in ifp ge-0/0/4.0, out ifp N/A sp 59009, dp 22, ip_proto 6, tos 0
Aug  3 01:28:23 01:28:23.434861:CID-0:THREAD_ID-01:RT: routed (x_dst_ip 10.1.0.129) from trust (ge-0/0/4.0 in 0) to ge-0/0/2.0, Next-hop: 10.0.1.129
Aug  3 01:28:23 01:28:23.434863:CID-0:THREAD_ID-01:RT:
  flow_first_policy_search: policy search from zone trust-> zone untrust (0x0,0xe6810016,0x16)
Aug  3 01:28:26 01:28:26.434137:CID-0:THREAD_ID-01:RT: packet dropped, denied by policy
Aug  3 01:28:26 01:28:26.434137:CID-0:THREAD_ID-01:RT: denied by policy Deny-Telnet(5), dropping pkt
Aug  3 01:28:26 01:28:26.434138:CID-0:THREAD_ID-01:RT: packet dropped, policy deny.
```

Which two statements are correct about the output shown in the exhibit. (Choose two.)

- A. The source address is translated.
- B. The packet is an SSH packet
- C. The packet matches a user-configured policy
- D. The destination address is translated.

Correct Answer: AB