

# NS0-181<sup>Q&As</sup>

NetApp Certified Storage Installation Engineer - ONTAP 9.1

## Pass NetApp NS0-181 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-181.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

You are a NetApp Professional Services engineer, employed by NetApp. You have just completed an ONTAP cluster installation. You need to collect the relevant configuration information to enable the Service Event Report (SER) to be created.

Which tool would you use to accomplish this task?

- A. Active IQ scheduled reports
- B. NetAppDocs output report
- C. ONTAP System Manager
- D. Active IQ Config Advisor worksheet

Correct Answer: A

---

### QUESTION 2

You are installing a 4-node AFF A400 cluster and are asked to create a custom security message before and after user login. Which two security features are used to perform this task? (Choose two.)

- A. EMS
- B. banner
- C. motd
- D. AutoSupport

Correct Answer: BD

---

### QUESTION 3

Click the Exhibit button.

```
Mar 18, 2020 07:35:35 CDT HA Group Notification (CLUSTER NETWORK DEGRADED) ALERT

Mar 19, 2020 22:04:20 CDT HA Group Notification (Health Monitor process cshm:
SwitchIfInErrorsWarn_Alert[NODE_NAME-sw1 (SWITCH_SERIAL_NUMBER)/Ethernet1/8]) ALERT

Mar 12, 2020 20:58:38 CDT HA Group Notification (Health Monitor process cshm:
SwitchIfInErrorsWarn_Alert[NODE_NAME-sw1 (SWITCH_SERIAL_NUMBER)/Ethernet1/8]) ALERT
```

Your ONTAP cluster shows the cluster network errors that are shown in the event log. What is used by ONTAP software to log the errors that are shown in the exhibit?

- A. SNMP

- B. AutoSupport
- C. BGP
- D. EMS

Correct Answer: D

**QUESTION 4**

You are setting up a new AFF A400 that will serve iSCSI LUNs. You will have four iSCSI SVMs that each need to connect to an Internet Storage Name Service (iSNS) for discovery and management purposes. In this scenario, which network interface is needed for each SVM to register with the name service?

- A. SVM data LIF
- B. SVM management LIF
- C. node management LIF
- D. intercluster LIF

Correct Answer: D

**QUESTION 5**

Click the Exhibit button.

```
cluster1::> network device-discovery show
```

Node/ Protocol	Local Port	Discovered Device	Interface	Platform
node1/cdp	e4a	switchA-NX.netapp.ccm (SSI142311PD)	e1/1/1-4	N3K-C3132Q-V
	e8a	switchA-NX.netapp.ccm (SSI142311PD)	e1/2/1-4	N3K-C3132Q-V
node2/cdp	e4a	switchB-NX.netapp.ccm (SSI142311PE)	e1/1/1-4	N3K-C3132Q-V
	e8a	switchB-NX.netapp.ccm (SSI142311PE)	e1/2/1-4	N3K-C3132Q-V

You are reviewing the setup of a recently installed FAS9000 switched cluster. As shown in the exhibit, the cluster interconnects are connected to a pair of Cisco Nexus 3132Q-V 40 Gb ports. For a high availability, which ports should swap Ethernet cables?

- A. Swap node1:e8a and node2:e4a.
- B. Swap node1:e4a and node1:e8a.

C. Swap node2:e4a and node2:e8a.

D. Swap node1:e4a and node2:e4b.

Correct Answer: C

[NS0-181 PDF Dumps](#)

[NS0-181 VCE Dumps](#)

[NS0-181 Braindumps](#)