

# NS0-506<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, Clustered Data  
ONTAP

## Pass NetApp NS0-506 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-506.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

A customer is experiencing slower than expected performance on a database connected to an iSCSI LUN. They are surprised that performance has decreased even though they have upgraded from a 1 GB to a 10 GB switch.

What are three causes for this problem? (Choose three.)

- A. Spanning Tree is incorrectly configured on the cluster nodes.
- B. There is a faulty cable or SFP in the data path.
- C. There is an MTU mismatch between the hosts, controllers, and switch.
- D. Flow control is incorrectly set on either the host or controllers.
- E. Routing is not set up between the iSCSI and cluster networks.

Correct Answer: ABC

---

### QUESTION 2

Exhibit

You have a 2-node data ONTAP 8.3 cluster.

Based on the exhibit, which change must be made to make svm1 conform to iSCSI best practices?

```
cl01::> net int show -vserver svm1 -data -protocol iscsi Logical Status Network Current Current Is Vserver Interface
Admin/Oper Address/Mask Node Port Home
```

```
svm1 up/up 10.204.34.25/24 cl01-01 a0a 434 true cl01::>iscsi show -vserver svm1 Vserver: svm1 Target Name:
iqn.1992 08.com.netapp: sn.ca5eaa069c211 Target Alias: svm1 Administrative Status: up
```

- A. The iSCSI LIFs must be moved to a VLAN higher than 1024.
- B. An iSCSI LIF must be added to node cl01-02.
- C. The Target Alias must be modified to match the Target Name.
- D. The iSCSI LIFs must be moved to a physical interface; iSCSI LIFs are not supported on top of an ifgrp.

Correct Answer: C

---

### QUESTION 3

Exhibit

```
cl01::>iscsi portal show Logical Status CurrCurr Vserver Interface TPGT Admin/Oper IP Address Node Port Enabled
svm1 1-a 1035 up/up
```

192.168.1.66 cl01-01 e0a true svm1 1-b 1051 up/up

192.168.1.67 cl01-01 e0b true svm1 2-a 1046 up/down

192.168.1.68 cl01-02 e0a true svm1 2-b 1052 up/up

192.168.1.69 cl01-02 e0b true

Referring to the exhibit, which action would you take to troubleshoot the iscsi-2-a interface?

- A. Verify that the iSCSI protocol is licensed for svm1.
- B. Cycle the upstream switch port down and back up again.
- C. Verify network connectivity between the host and LIF.
- D. Verify that the iSCSI protocol is started on svm1.

Correct Answer: B

---

#### QUESTION 4

Which information-gathering command should you use to gather logs for troubleshooting switch information for your Brocade switches?

- A. cfgshow
- B. fabricshow
- C. configshow
- D. supportsave

Correct Answer: B

---

#### QUESTION 5

You are zoning a fabric for a clustered Data ONTAP storage system. After cabling, you see the following addresses logged into the fabric: 20:04:00:a0:98:16:db:9c 50:0a:09:83:8d:b1:ce:c3 What should be included in the zone configuration?

- A. 50:0a:09:83:8d:b1:ce:c3 and the initiator WWNN
- B. 50:0a:09:83:8d:b1:ce:c3 and the initiator WWPN
- C. 20:04:00:a0:98:16:db:9c and the initiator WWPN
- D. 20:04:00:a0:98:16:db:9c and the initiator WWNN

Correct Answer: B

---

[NS0-506 VCE Dumps](#)

[NS0-506 Practice Test](#)

[NS0-506 Study Guide](#)