

NS0-515^{Q&As}

NetApp Certified Implementation Engineer - SAN, E-Series

Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-515.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Your company has deployed an E2824 and has decided to change the host protocol from iSCSI to FC. You use the storage array profile to review the installed SFPs.

In this scenario, which set of supported data rates indicates that you are using dual-purpose SFPs?

- A. 25 Gbps, 10 Gbps
- B. 32 Gbps, 16 Gbps, 8 Gbps, 4 Gbps
- C. 16 Gbps, 10 Gbps, 8 Gbps, 4 Gbps
- D. 16 Gbps, 8 Gbps, 4 Gbps

Correct Answer: C

Reference: https://library.netapp.com/ecm/ecm_download_file/ECMLP2773527 (2)

QUESTION 2

Which two errors would fail a pre-upgrade health check? (Choose two.)

- A. Hot spares are in use
- B. Volumes are reported on a non-preferred path
- C. An excess number of event log events are present
- D. I/O is being processed

Correct Answer: AC

Reference: https://kb.netapp.com/app/answers/answer_view/a_id/1029754/~/~how-to-upgrade-e-seriescontroller-firmware%2C-nvsram%2C-and-iom-firmware-using

QUESTION 3

What is the minimum number of drives needed to create a Dynamic Disk Pool?

- A. 12
- B. 8
- C. 3
- D. 11

Correct Answer: D

Reference: <https://www.netapp.com/us/media/tr-4652.pdf> (5)

QUESTION 4

A customer wants to manage an E-Series system over a secure connection between the system and a server. During implementation, you are asked to fulfill this installation requirement.

In this scenario, which three actions are required to complete this task? (Choose three.)

- A. Disable the legacy management interface on the system
- B. Disable all the system's local user roles except admin
- C. Import certificate authority signed certificates into the system
- D. Import the system's self-signed certificates into the system
- E. Complete the certificate signing request on the system

Correct Answer: ADE

QUESTION 5

A customer needs to add an EF280 with FC into its existing Brocade fabric but the FC ports in the SANtricity System Manager are showing the FC ports as down and the LED on the FC HIC is amber.

Which three tasks does the installer need to complete to solve this problem? (Choose three.)

- A. Verify that the ports are enabled on the switch
- B. Verify that the cables are plugged into the switch
- C. Verify that the server HBA has the boot BIOS enabled
- D. Verify that the EF280s management port is up
- E. Verify that the switch zone has the WWPNs for the EF280 and Server HBAs

Correct Answer: ABE

[NS0-515 PDF Dumps](#)

[NS0-515 VCE Dumps](#)

[NS0-515 Brindumps](#)