

NS0-515^{Q&As}

NetApp Certified Implementation Engineer - SAN, E-Series

Pass NetApp NS0-515 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-515.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A company implemented Automatic Load Balancing (ALB). When the controller workloads are monitored, it becomes obvious that there is an imbalance and that ALB is not working correctly.

In this scenario, what are two causes of the problem? (Choose two.)

- A. The company implemented a load balancing min-min algorithm that does not support ALB
- B. The company implemented an adaptive load balancing agent that does not support ALB
- C. The company implemented a host multipath driver that does not support ALB
- D. The company implemented a host type that does not support ALB

Correct Answer: CD

Reference: <https://mysupport.netapp.com/NOW/public/eseries/sam/index.html#page/GUID-8538272AB802-49D9-9EA2-96C82DAD26A2/GUID-90A829B6-ACEE-41C6-8595-91C7D90554EB.html>

QUESTION 2

An administrator is asked to migrate two DE6600 shelves into a newly deployed E5760 environment that is configured with a stack of two DE460C shelves.

In this scenario, how does the administrator complete this task?

- A. Cable the DE6600s at the beginning of the stack
- B. Cable the DE6600s into a separate stack
- C. Cable the DE6600s at the end of the stack
- D. Cable the DE6600s between the DE460C shelves

Correct Answer: C

Reference: https://library.netapp.com/ecm/ecm_download_file/ECMLP2773537

QUESTION 3

Which three factors should you consider before you install an E2860 in a data center? (Choose three.)

- A. current draw
- B. heat dissipation
- C. fire suppression capacity
- D. electromagnetic interference

E. ambient temperatures

Correct Answer: CBE

QUESTION 4

Your company has deployed an E2824 and has decided to change the host protocol from iSCSI to FC. You use the storage array profile to review the installed SFPs.

In this scenario, which set of supported data rates indicates that you are using dual-purpose SFPs?

- A. 25 Gbps, 10 Gbps
- B. 32 Gbps, 16 Gbps, 8 Gbps, 4 Gbps
- C. 16 Gbps, 10 Gbps, 8 Gbps, 4 Gbps
- D. 16 Gbps, 8 Gbps, 4 Gbps

Correct Answer: C

Reference: https://library.netapp.com/ecm/ecm_download_file/ECMLP2773527 (2)

QUESTION 5

A customer has launched a data analytics initiative and has been transferring old data into the new data lake. The customer has discovered some data read errors during the transfer process.

In this scenario, how should the customer have avoided these data integrity issues?

- A. by ensuring that data assurance and media scan are always activated
- B. by deploying secure-capable drives
- C. by turning on cyclic redundancy checks (CRCs)
- D. by turning on erasure coding

Correct Answer: A

[Latest NS0-515 Dumps](#)

[NS0-515 Practice Test](#)

[NS0-515 Study Guide](#)