

NSE7_EFW-6.4^{Q&As}

Fortinet NSE 7 - Enterprise Firewall 6.4

Pass Fortinet NSE7_EFW-6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/nse7_efw-6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Fortinet Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Examine the output of the `get router info ospf interface` command shown in the exhibit; then answer the question below.

```
# get router info ospf interface port4
port4 is up, line protocol is up
  Internet Address 172.20.121.236/24, Area 0.0.0.0, MTU 1500
  Process ID 0, Router ID 0.0.0.4, Network Type BROADCAST, Cost: 1
  Transmit Delay is 1 sec, State DROther, Priority 1
  Designated Router (ID) 172.20.140.2, Interface Address 172.20.121.2
  Backup Designated Router (ID) 0.0.0.1, Interface Address
  172.20.121.239
  Timer intervals configured, Hello 10.000, Dead 40, Wait 40, Retransmit
  5
    Hello due in 00:00:05
  Neighbor Count is 4, Adjacent neighbor count is 2
  Crypt Sequence Number is 411
  Hello received 106, sent 27, DD received 7 sent 9
  LS-Req received 2 sent 2, LS-Upd received 7 sent 5
  LS-Ack received 4 sent 3, Discarded 1
```

Which statements are true regarding the above output? (Choose two.)

- A. The port4 interface is connected to the OSPF backbone area.
- B. The local FortiGate has been elected as the OSPF backup designated router.
- C. There are at least 5 OSPF routers connected to the port4 network.
- D. Two OSPF routers are down in the port4 network.

Correct Answer: AC

on BROADCAST network there are 4 neighbors, among which 1*DR +1*BDR. So our FG has 4 neighbors, but create adjacency only with 2 (with DR and BDR). 2 neighbors DROther (not down).

QUESTION 2

Refer to the exhibits.

```
config vpn ipsec phase1-interface
edit "user-1"
    set type dynamic
    set interface "port1"
    set mode main
    set xauthtype auto
    set authusrgrp "Users-1"
    set peertype any
    set dhgrp 14 15 19
    set proposal aes128-sha256 aes256-sha384
    set psksecret <encrypted_password>
next
```

Which contain the partial configurations of two VPNs on FortiGate.

An administrator has configured two VPNs for two different user groups. Users who are in the Users-2 group are not able to connect to the VPN. After running a diagnostics command, the administrator discovered that FortiGate is not matching the user-2 VPN for members of the Users-2 group.

Which two changes must administrator make to fix the issue? (Choose two.)

- A. Use different pre-shared keys on both VPNs
- B. Enable Mode Config on both VPNs.
- C. Set up specific peer IDs on both VPNs.
- D. Change to aggressive mode on both VPNs.

Correct Answer: CD

QUESTION 3

What events are recorded in the crashlogs of a FortiGate device? (Choose two.)

- A. A process crash.
- B. Configuration changes.
- C. Changes in the status of any of the FortiGuard licenses.
- D. System entering to and leaving from the proxy conserve mode.

Correct Answer: AD

diagnose debug crashlog read

275: 2014-08-05 13:03:53 proxy=acceptor service=imap session fail mode=activated276: 2014-08-05

13:03:53 proxy=acceptor service=ftp session fail mode=activated277: 2014-08-05 13:03:53 proxy=acceptor service=nntp session fail mode=activated278: 2014-08-06 11:05:47 service=kernel conserve=on free="45034 pages" red="45874 pages" msg="Kernel279: 2014-08-06 11:05:47 enters conserve mode"280: 2014-08-06 13:07:16 service=kernel conserve=exit free="86704 pages" green="68811 pages"281: 2014-08-06 13:07:16 msg="Kernel leaves conserve mode"282: 2014-08-06

13:07:16 proxy=imd sysconserve=exited total=1008 free=349 marginenter=201283: 2014-08-06 13:07:16 marginexit=302

QUESTION 4

Examine the output from the `diagnose vpn tunnel list` command shown in the exhibit; then answer the question below.

```
#diagnose vpn tunnel list
name-Dial Up_0 ver=1 serial=5 10.200.1.1:4500->10.200.3.2: 64916 lgwy=static
nun=intf mode=dial_inst.bound if=2
parent=DialUp index=0
proxyid_um=1 child_num=0 refcnt=8 ilast=4 olast=4
stat: rxp=104 txp=8 rxb=27392 txb=480
dpd: mode=active on=1 idle=5000ms retry=3 count=0 segno=70
natt: mode=silent draft=32 interval= 10 remote_port=64916
proxyid= DialUp proto=0 sa=1 ref=2 serial=1 add-route
  src: 0:0.0.0.0.-255.255.255.255:0
  dst: 0:10.0.10.10.-10.0.10.10:0
  SA: ref=3 options= 00000086 type=00 soft=0 mtu=1422 expire =42521
replaywin=2048 seqno=9
life: type=01 bytes=0/0 timeout= 43185/43200
dec: spi=cb3a632a esp=aes key=16 7365e17a8fd555ec38bffa47d650c1a2
  ah=sha1 key=20 946bfb9d23b8b53770dcf48ac2af82b8ccc6aa85
enc: spi=da6d28ac esp=aes key=16 3dcf44ac7c816782ea3d0c9a977ef543
  ah=sha1 key=20 7cfde587592fc4635ab8db8ddf0d851d868b243f
dec:pkts/bytes=104/19926, enc:pkts/bytes=8/1024
```

Which command can be used to sniff the ESP traffic for the VPN DialUP_0?

- A. diagnose sniffer packet any `port 500`
- B. diagnose sniffer packet any `esp`
- C. diagnose sniffer packet any `host 10.0.10.10`

D. diagnose sniffer packet any `port 4500\`

Correct Answer: D

NAT-T is enabled. natt: mode=silentProtocol ESP is used. ESP is encapsulated in UDP port 4500 when NAT-T is enabled.

natt: mode=silent means IPSec is behind NAT (NAT traversal) <https://kb.fortinet.com/kb/documentLink.do?externalID=FD48755>

QUESTION 5

Which real time debug should an administrator enable to troubleshoot RADIUS authentication problems?

- A. Diagnose debug application radius -1.
- B. Diagnose debug application fnbamd -1.
- C. Diagnose authd console ?og enable.
- D. Diagnose radius console ?og enable.

Correct Answer: B

<https://kb.fortinet.com/kb/documentLink.do?externalID=FD32838>

[NSE7_EFW-6.4 Practice Test](#)

[NSE7_EFW-6.4 Study Guide](#)

[NSE7_EFW-6.4 Braindumps](#)