

# 300-625<sup>Q&As</sup>

Implementing Cisco Storage Area Networking (DCSAN)

## Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-625.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

A storage administrator is configuring inter-VSAN routing on a fabric that contains duplicate domain IDs. Which feature must be configured to ensure continued operation?

- A. auto topology
- B. transit VSANs
- C. IVR NAT
- D. virtual domains

Correct Answer: C

---

**QUESTION 2**

A storage administrator is upgrading Cisco NX-OS on a Cisco MDS switch. The administrator performs an ISSU upgrade following the configuration guide. While the install is proceeding, the administrator connects a new server to the switch, which cannot access storage. The existing servers continue to operate properly through the switch. Why is the new server failing to connect?

- A. The fabric data plane resets as part of the upgrade process.
- B. The new server is unable to log in to the fabric to receive an FC-ID.
- C. The upgrade process disables any currently unused ports.
- D. The zoning database is locked during the upgrade process.

Correct Answer: D

---

**QUESTION 3**

A storage network engineer is implementing disk-array data replication between two SAN environments in two different data centers not connected via Fibre Channel. Which SAN switch feature must be implemented?

- A. FCIP
- B. zoning merge over LAN
- C. VSAN scoping
- D. IVR

Correct Answer: A

---

**QUESTION 4**

Which condition requires using a device alias rather than a Fibre Channel alias?

- A. The zone database must be distributed over the fabric.
- B. The same alias must be used in zoning as well as DPVM.
- C. All aliases being used are being configured in the same VSAN.
- D. Aliases must be saved within a central database on the fabric.

Correct Answer: A

---

#### QUESTION 5

Which configuration is available only in Cisco DCNM-SAN Advanced mode?

- A. IVR
- B. VMpath configuration
- C. zoning
- D. template-based provisioning

Correct Answer: A

---

#### QUESTION 6

What does an unlicensed DCNM SAN fail to display?

- A. Fibre Channel, FCoE, and iSCSI topologies
- B. events and fault management
- C. historical performance monitoring
- D. real-time performance monitoring

Correct Answer: C

---

#### QUESTION 7

Refer to the exhibit.

```
switch-1 (config)# zoneset name Zone-B vsan 100
Zoning database update is progress, command rejected
```

Which command is used to determine which switch has the lock?

- A. show fcs ie vsan
- B. show zoneset active
- C. show zone status
- D. show flogi database

Correct Answer: C

### QUESTION 8

Refer to the exhibits.

#### Exhibit 1:

```
MDS-A# show zoneset vsan 100
zoneset name ZoneSetMDS-A-VSAN100- vsan 100
MDS-A# show zoneset brief vsan 100
zoneset name ZoneSetMDS-A-VSAN500 vsan 100
  zone Host1-Strg1
  zone Host2-Strg2
MDS-A# show zoneset active vsan 100
zoneset name ZoneSetMDS-A-VSAN100 vsan 100
  zone name Host1-Strg1 vsan 100
    pwwn 20:00:00:25:b5:fa:00:11
    pwwn 50:05:07:68:0d:05:ac:11
  zone name Host2-Strg2 vsan 100
    pwwn 20:00:00:25:b5:fa:00:22
    pwwn 50:05:07:68:0d:05:ac:22
MDS-A# show zone status vsan 100
VSAN: 100 default-zone: deny distribute: active only Interop: default
mode: basic merge-control: allow
session: none
hard-zoning: enabled broadcast: unsupported
smart-zoning: disabled
rscn-format: fabric-address
activation overwrite control: disabled
```

Output omitted for brevity

#### Exhibit 2:

```
MDS-A# show zoneset vsan 100
zoneset name ZoneSetMDS-B-VSAN100- vsan 100
  zone name Host3-Strg3 vsan 100
    pwwn 20:00:00:25:b5:fa:00:33
    pwwn 50:05:07:68:0d:05:ac:33
MDS-A# show zoneset brief vsan 100
zoneset name ZoneSetMDS-A-VSAN100 vsan 100
```

A storage network engineer activates a zoneset on MDS-A and verifies the successful activation (Exhibit 1). The engineer is then notified that there is a SAN outage (Exhibit 2) What is the cause of the outage?

- A. Another network engineer activated zoneset ZoneSetMDS-B-VSAN100 on MDS-A.
- B. Another network engineer issued the zone mode enhanced vsan 100 command on another switch in the fabric.
- C. Another network engineer activated the zoneset ZoneSetMDS-B-VSAN100 command on another switch in the fabric.
- D. Another network engineer issued the zone default-zone permit vsan 100 command on another switch in the fabric.

Correct Answer: D

**QUESTION 9**


DRAG DROP

Drag and drop the items from the left onto the correct descriptions on the right. Not all items are used.

Select and Place:

slow drain	port-to-port flow control
end-to-end flow control	prevents head-of-line blocking
buffer-to-buffer flow control	traffic failed to be transmitted at line rate
slow port	device that fails to accept frames at its line rate
virtual output queues	

Correct Answer:



**QUESTION 10**

Refer to the exhibit.

```
switch-2# show zone status vsan 10
VSAN: 10 default-zone: deny distribute: active only Interop: default
mode: enhanced merge-control: allow
session: cli [admin]
hard-zoning: enabled broadcast: enabled

Default zone:
qos: none broadcast: disabled ronly: disabled
```

A user who is logged in as an operator cannot update the zoneset. What is the cause of this issue?

- A. The fabric is locked by admin on switch-2.
- B. Hard zoning is enabled.
- C. Merge control is disabled.
- D. The switch has a conflicting domain ID.
- E. The fabric is locked by admin on another switch.

Correct Answer: A