

# 500-901<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Design

## Pass Cisco 500-901 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/500-901.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





#### **QUESTION 1**

Which primary functions are provided by VSANs?

- A. Independent fabric services per VSAN and zoning
- B. Software-based isolation of traffic and independent fabric services per VSAN
- C. Hardware-based isolation of traffic and independent fabric services per VSAN
- D. Specific driver configuration and FSPF routing

Correct Answer: A

#### **QUESTION 2**

What is a Universally Unique Identifier in the context of Cisco Unified Computing System?

- A. A unique identifier used to identify an object or entity on the internet.
- B. A unique identifier used in server profiles enabling server mobility.
- C. A unique identifier used in application profiles enabling server mobility.
- D. A unique identifier used in service profiles enabling server mobility.

Correct Answer: D

#### **QUESTION 3**

Which additional three traffic egress controls may be enabled in Cisco UCS Manager depending upon the network adapter selected? (Choose three.)

- A. Rate
- B. Best Effort
- C. Host Control
- D. Peak
- E. Burst
- F. Smooth

Correct Answer: BCE

#### **QUESTION 4**



- Which two VSANs are automatically created and cannot be deleted? (Choose two.)
- A. The Virtual Bridging VSAN
- B. The Isolated VSAN
- C. The Fabric Control VSAN
- D. The Default VSAN
- Correct Answer: BD

#### **QUESTION 5**

Which is a gap of first generation hyperconverged solutions addressed by Cisco HyperFlex?

- A. Integrated networking configuration during deployment
- B. Support for GPUs
- C. Support for multiple hypervisors
- D. Integrated firewall for security monitoring

Correct Answer: A

#### **QUESTION 6**

When can you use UCS Director to provision Service Profile template?

- A. For initial Service Profile template
- B. Always
- C. Never
- D. Only for updating Service Profile template

Correct Answer: A

### **QUESTION 7**

Which three statements describes Service Profiles?

- A. Service Profiles define a standard convention for WWNs agreed upon by all stakeholders for address blocks
- B. Service Profiles use Cisco\\'s OUI (00:25:B5) for the 3rd to 5th octets in WWN
- C. Service Profiles are only applicable to network configurations
- D. Service Profiles use the same hex value for 1st and 2nd octets in WWNN and WWPN



- E. Service Profiles are a logical view of a server without any tie to physical components
- F. Service Profiles are grouped by virtual machine operating system

Correct Answer: C

#### **QUESTION 8**

Cisco recommended to help customer\\'s provision physical, virtual, and multivendor data center infrastructure environments from a single pane?

- A. Cisco UCS Director
- B. Cisco UCS Performance Manager
- C. Cisco UCS Manager
- D. Cisco UCS Central

Correct Answer: C

#### **QUESTION 9**

An administrator is setting up a new VSAN and needs to use IVR to allow access to backup tape storage targets located in a different VSAN. There is an existing Nexus 5K switch in the SAN fabric that the admin would like to use; however, the switch is not IVR-enabled.

How can the Cisco Nexus switch be used?

- A. It cannot be used, since only MDS Switches implement IVR.
- B. As a Transit switch.
- C. As a Border switch or IVR NAT gateway.
- D. As an Edge switch.

Correct Answer: D

#### **QUESTION 10**

An administrator has configured an NPV traffic map for a new server interface, none of the uplinks in the traffic map are open action?

A. The traffic map will be disregarded and an uplink in the interface VSAN will be selected.

- B. The default VSAN uplink will be used if operational.
- C. The server will remain in a nonoperational state.
- D. The server interface will signal an FDISC message to the fabric switch.



Correct Answer: C

500-901 PDF Dumps

500-901 VCE Dumps

500-901 Practice Test