

A2090-544^{Q&As}

Assessment: DB2 9.7 Advanced DBA for LUW - Assessment

Pass IBM A2090-544 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/a2090-544.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

If you know that the table space containers for your database reside on RAID-5 3+p arrays, which registry variable should be assigned the value *:3 to help improve performance?

- A. DB2_APM_PERFORMANCE
- B. DB2_EXTENDED_IO_FEATURES
- C. DB2_RESOURCE_POLICY
- D. DB2_PARALLEL_IO

Correct Answer: D

QUESTION 2

Setting the DB2_FMP_COMM_HEAPSZ=0 will result in which the following?

- A. User-defined function calls will be disabled.
- B. In a partitioned environment, infinite communications will be enabled between partitions.
- C. In a partitioned environment, communications will not be buffered.
- D. Non-fenced routines can be invoked, however automatic database maintenance will be disabled.

Correct Answer: D

QUESTION 3

At which two levels can events be audited? (Choose two.)

- A. Instance level
- B. Database level
- C. Server level
- D. Operating System level
- E. Node level

Correct Answer: AB

QUESTION 4

If LOGSECOND=-1 then which of the following statements is true?

- A. You still use LOGPRIMARY and LOGFILSIZ configuration parameters to specify how many log files the database manager should keep in the active log path.
- B. You must configure the OVERFLOWLOGPATH configuration parameter if your active log path is not on a raw device.
- C. The database will reserve active log space for transactions that may need to roll back and write log records.
- D. An infinite number of overflow log files will be used with archival logging.

Correct Answer: A

QUESTION 5

A database recovery operation (RECOVER DATABASE) failed during the roll forward phase. The DBA wants to force the RECOVER DATABASE to redo the restore phase. What must occur to accomplish this?

- A. A RECOVER DATABASE command must be issued with the RESTART option specified.
- B. The RECOVER DATABASE operation must be terminated and a new RECOVER DATABASE command must be issued.
- C. A RECOVER DATABASE command must be issued with the TO END OF LOGS option specified.
- D. A RECOVER DATABASE command must be re-issued with the REPLACE option specified.

Correct Answer: A

QUESTION 6

What are two authorities and/or privileges required for replaying SQL audit logs? (Choose two.)

- A. SECADM authority
- B. EXECUTE privilege on audit routines with DATA
- C. DBADM authority
- D. EXECUTE privilege on audit routines with NO DATA
- E. SYSADM authority

Correct Answer: AB

QUESTION 7

Which registry variable allows you to limit the size of individual containers for automatic storage table spaces?

- A. DB2_LIMIT_AS_CONTAINER_BLOCKS
- B. DB2_SET_MAX_CONTAINER_SIZE

- C. DB2_ALLOCATION_SIZE
- D. DB2_TRUNCATE_AS_STORAGE

Correct Answer: B

QUESTION 8

A journaling application inserts data with continually increasing sequential keys while a clean up process randomly deletes erroneous rows. What can be done to maximize insert performance?

- A. Issue a db2set DB2MAXFSCRSEARCH=1024 command.
- B. Issue an ALTER TABLESPACE EXTEND statement.
- C. Issue a db2set DB2SKIPDELETED=ON command.
- D. Issue an ALTER TABLE APPEND ON statement.

Correct Answer: D

QUESTION 9

A database named MYDB is created in instance DB2INST1, which has been configured to use KRB_SERVER_ENCRYPT authentication. If a client attempting to access database MYDB does not support Kerberos authentication, which authentication method will be used to establish a connection?

- A. SERVER_ENCRYPT
- B. SERVER
- C. KRB_SERVER_ENCRYPT
- D. CLIENT

Correct Answer: A

QUESTION 10

A DBA needs to create a federated database and configure access to join data from three Oracle instances and one DB2 database. Which objects are needed to establish the specified connections?

- A. 1 Oracle server , 1 DB2 server , 3 Oracle wrappers , and nicknames for each database
- B. 1 Oracle server , 1 DB2 server , 1 Oracle wrapper , 1 DB2 wrapper , and nicknames for each database
- C. 3 Oracle servers , 1 DB2 server , 3 Oracle wrappers , 1 DB2 wrapper , and nicknames for each database
- D. 3 Oracle servers , 1 DB2 server , 1 Oracle wrapper , 1 DB2 wrapper , and nicknames for each database

Correct Answer: D

QUESTION 11

What steps, in the correct order, are performed by the SQL and XQuery compilers to generate executable code for non-federated queries?

- A. parse query; rewrite query; check semantics; pushdown predicates; execute access plan
- B. check semantics; parse query; rewrite query; build access plan
- C. parse query; check semantics; rewrite query; build access plan
- D. check semantics; parse query; build access plan; pushdown predicates; execute access plan

Correct Answer: C

QUESTION 12

How can a DBA validate that an existing backup was compressed?

- A. Check the output from the command LIST HISTORY BACKUP ALL FOR the database.
- B. Check the value of the COMPRESS_BACKUP database configuration setting.
- C. Check the value of the DB2_COMPRESS_BACKUP registry variable.
- D. Check the header information of the backup file using db2ckbkp.

Correct Answer: D

QUESTION 13

What is required to successfully use the check backup utility (db2ckbkp)?

- A. system administrator authority
- B. read permission on the database
- C. system maintenance authority
- D. read permission on the backup image

Correct Answer: D

QUESTION 14

Which command will back up a database named SAMPLE to a TSM server using two concurrent TSM client sessions?

- A. BACKUP DATABASE sample USE TSM OPEN 2 SESSIONS WITH 4 BUFFERS

- B. BACKUP DATABASE sample USE TSM OPEN 4 SESSIONS WITH 2 BUFFERS
- C. BACKUP DATABASE sample USE TSM OPEN 2 SERVERS WITH 4 BUFFERS
- D. BACKUP DATABASE sample USE TSM OPEN 4 SERVERS WITH 2 BUFFERS

Correct Answer: A

QUESTION 15

In order for HADR to start, which statement is true when setting the HADR_TIMEOUT database configuration value?

- A. The HADR_TIMEOUT value must be identical on both the primary and the standby server.
- B. Changes to the HADR_TIMEOUT value will take effect immediately.
- C. If the HADR_TIMEOUT value is set to -1, connection timeouts will not occur.
- D. If the HADR_TIMEOUT value is different between the two servers, the lowest value is used.

Correct Answer: A

[Latest A2090-544 Dumps](#)

[A2090-544 VCE Dumps](#)

[A2090-544 Practice Test](#)