

C4090-454^{Q&As}

IBM High-End Tape Technical Solutions V7

Pass IBM C4090-454 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/c4090-454.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which resource typically contains product installation and planning checklists?

- A. IBM Redbooks
- B. IBM White Papers
- C. Product Operations Guide
- D. Solutions Assurance Product Review Guides

Correct Answer: D

QUESTION 2

Which IBM tape solution can be shared as a Tape Backup Infrastructure for System z with DESMSd55, System i with BRMS and Red Hat Linux with NBU\?

- A. IBM Virtualization Engine TS7740
- B. IBM TS1140 with 007 Tape Controller
- C. IBM System Storage TS3500 Tape Library
- D. IBM System Storage T53310 Tape Library

Correct Answer: C

QUESTION 3

What is the key advantage of the IBM TS7720 over the EMO DLM?

- A. Larger maximum capacity
- B. Virtual drive scalability up to 256
- C. Supports bi-directional replication in a grid
- D. Deduplication which does not use hashing algorithms

Correct Answer: C

QUESTION 4

A service provider has two separate customers on different LPARS using a TS7740 and wants to ensure that neither customer can access the other customer's data from the host. Which of the following features, functions or processes

would be recommended to achieve this?

- A. Use IODF and SDAC to prevent access to volume ranges by Libport ID
- B. Create separate partitions within the TS7700 using the categories defined in the DEVSUP member
- C. The functions DAA and SAA will work with JES2 on z/OS to direct workloads to the correct cluster
- D. Create separate physical cartridge pools so each customer's data resides on a different cartridge range

Correct Answer: A

QUESTION 5

Which two are types of nodes in the TS7700 Virtualization Engine architecture? (Select two)

- A. hNode
- B. vNode
- C. sNode
- D. pNode
- E. tNode

Correct Answer: AB

QUESTION 6

A customer has two TS7740 V07 at Release 3 in a two-way grid across two sites. There is a new requirement for a subset of the data created in Site A (Cluster 0) to be written in both sites but to be in Site B (Cluster 1) at the end of the job. What method is best employed to achieve this with the least impact on the batch run, and at the lowest cost?

- A. Setup a policy for the data creating a copy consistency of RR in Site A
- B. Setup a policy for the data creating a copy consistency of RD in Site A
- C. Set up a policy for the data creating a copy consistency of DR in Site A
- D. Connect Site A to the TS7740 in Site B with two PICON channels and run the jobs using logical units on Site B

Correct Answer: C

QUESTION 7

What drive types are supported in the IBM TS3300 Tape Library?

- A. LTO drives only

- B. TS11x0 drives only
- C. Both LTO and DLT drives
- D. Both LTO and TS11x0 drives

Correct Answer: B

QUESTION 8

What is a valid implementation for in-band encryption in z/OS using TS1 130 or TS1140 drives?

- A. LME with TS7700 and encryption configuration feature
- B. AME with TS1130 and appropriate software and device driver
- C. SME with 007 controller and CU encryption configuration feature
- D. LME with C07 controller and CU encryption configuration feature

Correct Answer: C

QUESTION 9

On a TS3500 Tape Library, what is the minimum number of cartridge cells that can be configured in an L23 frame?

- B. 58
- C. 117
- D. 248

Correct Answer: B

QUESTION 10

To what value should the missing interrupt handler (MIH) be set for 3592 tape drives?

- A. 93 minutes
- B. 39 minutes
- C. Auto set by the system
- D. set explicitly to "disabled"

Correct Answer: C

QUESTION 11

A newly installed TS7720 Virtualization Engine has recently been integrated into a three-way grid. The logical volumes created in the other two systems are not properly being replicated to the new system. All local IBM and customer support resources have been exhausted in trying to determine the cause with no resolution in sight. What should be the next step to try to resolve the issue via IBM?

- A. Contact local PSR to escalate
- B. Contact the local SSR to escalate
- C. Contact the local software provider to escalate
- D. Contact the sales representative to escalate

Correct Answer: D

QUESTION 12

A banking customer's TS7740 was unable to replicate the tape backup data to the DR data center via the current grid network. The IBM support engineer had created a PMR with Severity 1 because the tape library is supporting the customer's production environment. Six hours after the PMR was created, IBM Level 2 support requested to change the Severity Level to 2, even though the problem had not been resolved. Based on IBM guidelines, why would this problem need to be reduced to Severity 2?

- A. Severity 1 only applies to Tape Failure
- B. Severity 1 only applies to Network Failure
- C. Severity 1 only applies to Production Failure
- D. Severity 1 problem must be resolved within 6 hours

Correct Answer: C

QUESTION 13

A newly installed TS7720 Virtualization Engine has recently been integrated into a three-way grid. The logical volumes created in the other two systems are not properly being replicated to the new system. All local IBM and customer support resources have been exhausted in trying to determine the cause with no resolution in sight. What should be the next step to try to resolve the issue via IBM?

- A. Contact local PSR to escalate
- B. Contact the local SSR to escalate
- C. Contact the sales representative to escalate
- D. Contact the local software provider to escalate

Correct Answer: C

QUESTION 14

According to the IBM TS7700 Performance white paper, why does it show that a T67720 has only a sustained I/O performance and a TS7740 has a sustained AND peak I/O performance?

- A. Disk is faster than tape
- B. A disk-based repository delivers more constant throughput rates
- C. The TS7740 has to do pre-migration tasks at a certain point of operation
- D. The TS7740 Fibre Channel disk cache does filesystem rebuilds from time to time

Correct Answer: C

QUESTION 15

What is the maximum supported distance for inter-TS7700 cluster grid links without Ethernet extenders?

- A. 10 km
- B. 100 km
- C. 250 km
- D. > 1000 km

Correct Answer: A

[Latest C4090-454 Dumps](#)

[C4090-454 PDF Dumps](#)

[C4090-454 Practice Test](#)