

HP2-T26^{Q&As}

Servicing HP BladeSystem Solutions

Pass HP HP2-T26 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp2-t26.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which resource can be used to identify the warranty status of an HP BL460c G6 Server Blade?

- A. IT Resource Center
- B. HP Service Advisory
- C. HP Onboard Administrator
- D. HP Service Dashboard

Correct Answer: D

QUESTION 2

What is used to update firmware on several HP VC Ethernet or Fibre Channel modules simultaneously?

- A. VCM
- B. HP FDT
- C. VCSU
- D. OA

Correct Answer: C

QUESTION 3

A customer is experiencing intermittent storage connectivity issues in their BladeSystem environment. After collecting the log files from the external storage system and the interconnects, you determine the problem is in the Onboard Administrator configuration.

Which step should you take next in the troubleshooting process?

- A. Implement preventive measures.
- B. Initiate the replacement procedure of the midplane.
- C. Plan the repair procedure.
- D. Verify if the solution is covered by a carepack.

Correct Answer: C

QUESTION 4

How often does the Hardware Status Polling task within HP SIM check communications status with all discovered devices?

- A. Servers and non-servers are checked every five minutes
- B. Servers and non-servers are checked every ten minutes
- C. Servers are checked every five minutes; non-servers are checked every ten minutes
- D. Servers are checked every ten minutes; non-servers are checked every five minutes

Correct Answer: B

QUESTION 5

Which HP mezzanine option supports hardware RAID for Solid State Drives (SSDs)?

- A. HP PCI Express Mezzanine Pass-Thru card
- B. HP StorageWorks IO Accelerator
- C. HP Smart Array P712m Controller
- D. HP Smart Array P700m Controller

Correct Answer: C

QUESTION 6

How is a backup of the Onboard Administrator (OA) performed?

- A. by using the CLI of interconnect in bay 1
- B. by using the GUI
- C. by copying the activeoa.cfg file to the USB drive
- D. by recording the configuration on a CD using CD-RW attached to the OA USB port

Correct Answer: B

QUESTION 7

An HP VC Flex-10 module must be replaced in a c3000 BladeSystem enclosure because one uplink port is defective.

What must be done before physically replacing the module?

- A. Back up the enclosure EBIPA information.
- B. Copy the server profiles to a flash drive.

- C. Copy the VCM logs to a flash drive.
- D. Back up the Virtual Connect settings.

Correct Answer: D

QUESTION 8

Place each deployment method next to its description.

Select and Place:

	Descriptions		
place here	Server boots to an environment where normal operations cannot occur until firmware updates complete.		
place here	Installation tool runs on the physical hardware.		
place here	Installation tool runs on one system but updates other physical targets.		
place here	Installation runs while the host processor is running in the customer's normal environment.		
Offline	Remote	Online	Local

Select and Place:

	Descriptions	
place here	Server boots to an environment where normal operations cannot occur until firmware updates complete.	
place here	Installation tool runs on the physical hardware.	
place here	Installation tool runs on one system but updates other physical targets.	
place here	Installation runs while the host processor is running in the customer's normal environment.	
Offline	Remote	Online Local

Correct Answer:

	Descriptions	
Offline	Server boots to an environment where normal operations cannot occur until firmware updates complete.	
Local	Installation tool runs on the physical hardware.	
Remote	Installation tool runs on one system but updates other physical targets.	
Online	Installation runs while the host processor is running in the customer's normal environment.	

QUESTION 9

Which Advanced Memory Protection (AMP) features are available on a ProLiant BL460c G6? (Select three.)

- A. Memory Non-Lock-Step mode
- B. online replace and addition memory
- C. advanced error checking and correcting
- D. hot plug RAID memory
- E. online spare memory
- F. mirrored memory

Correct Answer: CEF

QUESTION 10

Why should an electrostatic discharge (ESD) wrist strap be used when replacing parts such as memory DIMMs?

- A. ESD protection is built into the equipment, so an ESC wrist strap is not needed.
- B. A 48 V DC PSU will contribute to higher static electricity.
- C. It prevents the part from being damaged by static electricity.
- D. A current of more than 75 mlcan kill someone.

Correct Answer: C

QUESTION 11

What can be used to reboot the Active or Standby Onboard Administrator (OA) module?

- A. ASR implemented on the OA level
- B. enclosure link-down port
- C. enclosure Reset button at the rear of the enclosure
- D. Insight Display

Correct Answer: C

QUESTION 12

HP Power Protector is used for which purpose?

- A. preventing the overload of a power supply unit in a c7000 enclosure
- B. making a backup of the system disk
- C. power capping of a c7000 enclosure
- D. monitoring and managing the R7000 UPS

Correct Answer: D

QUESTION 13

A c7000 enclosure is fully populated with power supplies. Each power supply will have 2400W available if the N+1 power mode is configured. What is the total amount of available power?

- A. 7200W
- B. 12000W
- C. 14400W
- D. 16800W

Correct Answer: C

QUESTION 14

A server blade has a memory error. All the LEDs in all the banks are illuminated. What should you do first to address this issue?

- A. Simultaneously replace the memory in all the banks.
- B. Replace the system board that the memory is connected to.
- C. Replace the processor, which is causing a false memory error.
- D. Replace one memory bank at a time.

Correct Answer: D

QUESTION 15

How can you generate a report that contains a detailed set of information about a specific enclosure including configuration and event logs?

- A. Use HP System Management Homepage of a blade in bay 1.
- B. Use Insight Display to save a configuration file to the USB key.
- C. Use HP SIM to save a configuration file.

D. Use the show all command from the Onboard Administrator CLI.

Correct Answer: D

[HP2-T26 VCE Dumps](#)

[HP2-T26 Study Guide](#)

[HP2-T26 Exam Questions](#)