

MA0-101^{Q&As}

McAfee Certified Product Specialist - NSP

Pass McAfee MA0-101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ma0-101.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by McAfee
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Malware Protection requires which of the following feature or features to be enabled?

- A. HTTP response scanning
- B. Attack Filters
- C. Performance Monitoring
- D. The "Default Inline IPS" policy

Correct Answer: A

QUESTION 2

As a recommended best practice, what is the total number of sensors that should be managed through a single Network Security Manager installation?

- A. 25
- B. 50
- C. 75
- D. 100

Correct Answer: B

QUESTION 3

Which of the following rules do sub-interfaces inherit when they are created?

- A. ACL rules
- B. Sensor rules only
- C. Port rules only
- D. Sensor and port rules

Correct Answer: D

QUESTION 4

Which logs are used to determine who was logged into the Manager the last time a signature set update was pushed from the Manager to the Sensor?

- A. Trace log

- B. Fault log
- C. Manager ems log
- D. User Activity Audit log

Correct Answer: D

QUESTION 5

Which of the following deployment modes receives a copy of the packet from a mirrored switch port?

- A. Redundant
- B. SPAN
- C. TAP
- D. In-line

Correct Answer: B

QUESTION 6

Which of the following commands will reestablish the Alert and packet log channel connection between the sensor and manager?

- A. Connectalertandpktlogchannels
- B. Disconnectalertandptologchannels
- C. reconnectalertandpktlogchannels
- D. deinstall

Correct Answer: C

QUESTION 7

In L3 mode, a sensor detects an L2 device based on which address?

- A. MAC
- B. IP
- C. Default Gateway
- D. DNS

Correct Answer: B

QUESTION 8

If the Health level of a Host cannot be determined. McAfee NAC assigns which of the following System Health levels to that Host?

- A. Fair
- B. Poor
- C. Serious
- D. Unknown

Correct Answer: D

QUESTION 9

What type of encryption is used for alert channel (control channel) communication between the Sensor and the Manager?

- A. SSL with RC4
- B. SSL with MD5
- C. SSL with RC4 and MD5
- D. DES

Correct Answer: C

QUESTION 10

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

Correct Answer: C

QUESTION 11

Which of the following CLI commands only removes trust between a sensor and manager?

- A. Resetconfig
- B. Deletesignatures
- C. Factorydefaults
- D. Deinstall

Correct Answer: D

QUESTION 12

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

- A. Signature based
- B. Pattern matching
- C. Denial of Service
- D. Remediation

Correct Answer: C

QUESTION 13

Which of the following are considered part of the Operational mode of System Health-based NAC? (Choose three)

- A. Audit
- B. IPS
- C. TAP
- D. Simulation
- E. Enforcement
- F. SPAN

Correct Answer: ADE

QUESTION 14

Which of the following CLI commands removes trust between a sensor and manager, removes signatures and restores default port settings, but retains IP configuration?

- A. Resetconfig
- B. Deletesignatures

C. Factotydefaults

D. Deinstall

Correct Answer: A

QUESTION 15

_____ are a set of Access Control List (ACL) rules that define network access provided to a host, subject to Network Access Control.

A. Network Access Lists

B. Network Access Objects

C. Network Access Zones

D. Network Access Policy

Correct Answer: C

[Latest MA0-101 Dumps](#)

[MA0-101 PDF Dumps](#)

[MA0-101 Braindumps](#)