

H12-831^{Q&As}

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

Pass Huawei H12-831 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/h12-831.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

A campus deploys both IPv4 and IPv6 networks for service testing, and runs IS-IS to realize network interconnection. The IS-IS routing protocol has good scalability and is widely used in the existing network. Which of the following statements is true about IS-IS scalability?

A. IS-ISuseTLVstructure builds the message so thatIS-ISMore flexibility, flexibility and scalability

B. forIS-ISIn terms of adding new features, only adding newTLVJust

C. IS-ISto supportPV6to addTLVcarryPv6Address information

D. N LPIDYesIS-ISto supportIPv6an addedTLV

Correct Answer: ABC

QUESTION 2

As shown below:

<ra>displa</ra>	y ospf Isdb						
	OSPF Process 1 with Router (D 1 72.16-1.1						
1Typ*- Router .Ro—T ,	Link State Database			# 1 1 1 1 1 1 1 1			
		Area: 0.0,0,0		1 1 1 1 1 1 1			
	LinkState ID	AdvRouter	Age	LenSequence		Metric	
	17216.1.3	172.16.1.3	216	60	B0000000	1	
	72 16.1,2	172.1 2	214	60	80000008		
	17X16 1 1		217	60	80000007		
	r	1 *1		1	s00000c)^>		
		1 々 1& 1."		1	member-	0	
Network	10/1.13.2	1 7N16.1.m	218	32	80000001	0	
Network	161.12.2	172J6.1 2	21 8	32	80000001	0	
Network	10.1.34.2	172.1 6.1 A	209	32	80000002	0	

A. area. have8indivualMAThe internet

B. area. have4indivualMAThe internet

C. area. have4router

D. area. have8router

Correct Answer: BC

QUESTION 3

Which of the following reasons may cause the hosts in the same--VLAN LAN to fail to communicate with each other?

- A. port isolation is configured on the switch
- B. the wrong port is configured on the machine, andMA, Caddress binding
- C. interface is artificialshutdownor the physical interface is damaged
- D. switchMA, Caddress learning errors

Correct Answer: ABCD

QUESTION 4

In what ways can log information be viewed:

- A. Network management system interface view
- B. log in to the device viadisplay logbuferCheck
- C. there is no way
- D. Willflash:/logfile/Tlog file viaFIP/TFTPtransfer toPCsuperior

Correct Answer: ABD

QUESTION 5

When a fault occurs, the fault can be classified to reduce the scope of fault location. Which of the following is not an interface configuration fault?

- A. Inconsistent duplex modes of interfaces on both ends
- B. IPaddress conflict
- C. Interface authentication is inconsistent
- D. Inconsistent luminous power at both ends


Correct Answer: D

QUESTION 6

Drag and Drop

2023 Latest pass2lead H12-831 PDF and VCE dumps Download

The configuration shown is performed on R2 to filter all incoming routes. Suppose there is a BGP route with the AS_Path attribute of [100200300400] on R1 that needs to be sent to R2. Please help the network administrator to adjust the AS order in the AS_Path attribute of the route on R1 to ensure that the route entry will not be filtered by the routing policy of R2_____, ____, ____, ____.



Select and Place:



Correct Answer:

2023 Latest pass2lead H12-831 PDF and VCE dumps Download



QUESTION 7

Which of the following statements is false when troubleshooting the dual-active failure of a VRRP backup group?

- A. No need to check deliveryVRRPWhether the switch port of the advertisement message is in the sameVLAN
- B. need to check the interfaceVRRPGroupIDIs it the same
- C. Interface needs to be checkedIPWhether the address is in the same network segment
- D. need to checkVRRPgroup of virtualIPIs the address the same

Correct Answer: A

QUESTION 8

After the VLAN-based MA, C address flapping detection function is configured, if the MA, C address flaps. The interface can be configured to perform actions according to requirements. Which of the following is NOT a configurable action?


- A. Traffic filtering
- B. send alert
- C. interface blocking
- D. MA, Caddress blocking

Correct Answer: A

QUESTION 9

As shown in the figure, all interfaces of the router enable DSPF. The cost value of the link is marked in the figure. R2

The LoopbackD interface is advertised in area 1, then the cost of R1 reaching 10.2/32 is?



A. 200

B. 150

C. 50

D. 100

Correct Answer: A

QUESTION 10

Link LSAs of OSPFv3 are propagated throughout the area.

A. right

B. wrong

Correct Answer: B

QUESTION 11

The routing policy tools that can be used by BGP mainly include Filterpolicy and oRoute- policy. Fiterpolicy can only



filter routes, Rote - policy can only modify routes.


A. True

B. False

Correct Answer: B

QUESTION 12

As shown in the figure, in a medium-sized network, BGP generally deploys dual RRs to improve R reliability. When deploying dual RRs, the Cluster IDs of the two RRs are generally set to be the same. The reason for this is



- A. Prevent RR from receiving too many routes and causing insufficient memory
- B. prevent suboptimal
- C. prevent loops
- D. Prevent the client from receiving too many routes and causing it to run out of memory

Correct Answer: A

QUESTION 13

Since BGP is an EGP routing protocol, BGP routing policies can only be deployed between EBGP neighbors. The routing policy deployed between IBGP neighbors is invalid.

- A. True
- B. False



2023 Latest pass2lead H12-831 PDF and VCE dumps Download

Correct Answer: B
QUESTION 14
In OSPFv3, an LSA whose propagation range is one area haskind. (Fill in Arabic numerals only)
A. 6
B. 7
C. 8
D. 9
Correct Answer: D

QUESTION 15

In an MPLS domain, LSR can be divided into Ingress LSR, Transit LSR and Egress LSR according to the different processing methods of LSRs for data. For the same FEC. a certain LSR can be the Ingress LSR of the FEC or the Transit LSR of the FEC. LSRO

A. True

B. False

Correct Answer: B

Latest H12-831 Dumps

H12-831 Practice Test

H12-831 Study Guide