NS0-194 ^{Q&As}

NS0-194^{Q&As}

NetApp Certified Support Engineer

Pass NetApp NS0-194 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/ns0-194.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

![Pass2Lead](https://Pass2Lead.com)
QUESTION 1

A customer asks what is the correct way to configure an ONTAP system for multi-tenancy. The customer wants to serve data and also protect data using SnapMirror from tenant A using network A and from tenant B using network B.

In this scenario, which statement is correct?

A. The customer must use different VLANs for the two tenants.

B. This setup can only work if tenant A and tenant B use a shared network infrastructure.

C. The customer must set up two different IPspaces for the two tenants.

D. Each node can only communicate with tenant A or tenant B, but not with both at the same time.

Correct Answer: B Section: (none)

QUESTION 2

Source Path Destination Path Relationship ID Relationship Type msgld: msragld:
78e304e0-9781-1234-abcd-00a098d771bd XDP msxpgld: msraxpgld: 3ca42ab4-9782-1234-abcd-00a098d771bd XDP
na_docavgld: ndradocavgld: a4b233b2-9783-1234-abcd-00a098d771bd XDP na_dr: ndradr:
c97d36a0-6d7c-11e8-83fb-00a098d771bd XDP na_gld: ndragld: 9e7e034d-9782-1234-abcd-00a098d771bd XDP
na_mpgld: ndrampgld: 16e52e0d-9783-1234-abcd-00a098d771bd XDP na_opengld: ndraopengld:
dabb1813-9780-1234-abcd-00a098d771bd XDP na_poc: ndrapoc: c1d632d7-977b-1234-abcd-00a098d771bd XDP
na_pubgld: ndrapubgld: 1a3f866c-9780-1234-abcd-00a098d771bd XDP

Referring to the output, which type of SnapMirror destination relationship is being used?

A. Single Volume SnapMirror Asynchronous

B. Single Volume SnapMirror Synchronous

C. SnapVault

D. Storage Virtual Machine DR

Correct Answer: A Section: (none)

QUESTION 3

You want to use the supported method to upgrade the ONTAP version of a Cloud Volumes ONTAP instance from ONTAP 9.5 to ONTAP 9.6.

In this scenario, which NetApp tool accomplishes this task?

A. Cloud Manager

B. Cloud Insights

C. Active IQ Unified Manager

![Pass2Lead logo](https://Pass2Lead.com)
D. ONTAP System Manager

Correct Answer: D Section: (none)

Reference: https://docs.netapp.com/us-en/occm/task_updating_ontap_cloud.html#suspending-snapmirrortransfers

QUESTION 4

Workload	ID	Latency	Network	Cluster	Data	Disk	QoS	NVRAM	Cloud
-total-		110.35ms	327.00us	327.00us	0ms				
110.02ms	0ms	0ms	0ms						
vs1vol0	111	167.82ms	603.00us	603.00us	0ms				
167.22ms	0ms	0ms	0ms						
vol1	1234	117.76ms	191.00us	191.00us	0ms				
117.56ms	0ms	0ms	0ms						
vol2	999	44.24ms	190.00us	190.00us	0ms	44.05ms	0ms	0ms	0ms
-total-	-								
38.89ms	256.00us	256.00us	0ms	38.63ms	0ms	0ms	0ms		
vol2	999	64.47ms	266.00us	266.00us	0ms	64.20ms	0ms	0ms	0ms
vol1	1234	27.28ms	253.00us	253.00us	0ms	27.03ms	0ms	0ms	0ms
vs1vol0	111	23.72ms	249.00us	249.00us	0ms	23.47ms	0ms	0ms	0ms
-total-	-	409.81ms	169.00us	169.00us	0ms				
409.65ms	0ms	0ms	0ms						
vol1	1234	816.92ms	120.00us	120.00us	0ms				
816.80ms	0ms	0ms	0ms						
vol2	999	407.88ms	219.00us	219.00us	0ms				
407.66ms	0ms	0ms	0ms						
vs1vol0	111	3.68ms	193.00us	193.00us	0ms	3.49ms	0ms	0ms	0ms

Referring to the exhibit, which two components should be examined? (Choose two.)

A. cluster switches

B. SAS adapter

C. network interface card

D. disk

Correct Answer: BD Section: (none)

QUESTION 5

A disaster causes a FlexGroup volume to be unrecoverable, but it was protected by a SnapMirror relationship. You solve the issue, and the source is operational. Now, you want to return to serving the data from the original source.

In this scenario, what do you do next?

A. Initialize the SnapMirror relationship.

B. Restore data from a backup copy.

C. Perform a SnapMirror update.

D. Delete the SnapMirror relationship.

![Pass2Lead](https://Pass2Lead.com)
Correct Answer: A Section: (none)

Reference: https://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.pow-fg-mgmt%2FGUID576192B0-18B8-40D3-AA3E-FC34415DC4F7.html

QUESTION 6

You are using FCP and iSCSI protocols from your clients with ONTAP as the target. You want to ensure that storage failover (SFO) works correctly for your clients.

In this scenario, which two features on the initiator and the target will accomplish this task? (Choose two.)

A. LACP

B. MPIO

C. ALUA

D. SCSI

Correct Answer: BC Section: (none)

Reference: https://www.netapp.com/media/10680-tr4080.pdf

QUESTION 7

A customer is trying to enable NVMe and wants to use the FC adapters in the controllers but cannot enable the protocol.

![Pass2Lead](https://Pass2Lead.com)
```
aff::> fcp adapter show -fields node, adapter, physical-protocol, max-speed, status-
admin, media-type, speed
  (network fcp adapter show)

node       adapter  physical-protocol  max-speed  status-admin  media-type  speed
--------   -------  -----------------  ---------  ------------  ----------  --------
aff-01     0e       fibre-channel      16         up            ptp         auto
aff-01     0g       fibre-channel      16         up            ptp         auto
aff-01     0h       fibre-channel      16         up            ptp         auto
aff-01     1a       fibre-channel      16         up            ptp         auto
aff-01     1b       fibre-channel      16         up            ptp         auto
aff-01     2a       fibre-channel      16         up            ptp         16
aff-01     2b       fibre-channel      16         up            ptp         16
aff-01     3a       fibre-channel      16         up            ptp         auto
aff-01     3b       fibre-channel      16         up            ptp         auto
aff-01     4a       fibre-channel      16         up            ptp         auto
aff-01     4b       fibre-channel      16         up            ptp         auto
aff-02     0e       fibre-channel      16         up            ptp         auto
aff-02     0f       fibre-channel      16         up            ptp         auto
aff-02     0g       fibre-channel      16         up            ptp         auto
aff-02     0h       fibre-channel      16         up            ptp         auto
aff-02     1a       fibre-channel      16         up            ptp         auto
aff-02     1b       fibre-channel      16         up            ptp         auto
aff-02     2a       fibre-channel      16         up            ptp         auto
aff-02     2b       fibre-channel      16         up            ptp         auto
aff-02     3a       fibre-channel      16         up            ptp         auto
aff-02     3b       fibre-channel      16         up            ptp         auto
aff-02     4a       fibre-channel      16         up            ptp         auto
aff-02     4b       fibre-channel      16         up            ptp         auto
```

Referring to the exhibit, what is causing the problem?

A. There are no FC adapters installed with the speed set to 32Gbps.

B. There are no FC adapters installed with a physical protocol set to NVMe.

C. There are no FC adapters installed with a max-speed of 32Gbps.

D. There are no FC adapters installed with a media type of NVMe.

Correct Answer: B Section: (none)

QUESTION 8

A customer ordered a FAS2720 cluster with 8 TB SATA drives. The customer wants to use the Advanced Drive Partitioning (ADP) feature to avoid consuming the high capacity drives for the root aggregate. Before you use the cluster setup, you issue the aggr status command and notice that ADP is not being used.

In this scenario, what would you use to implement ADP?

A. loader prompt

B. special boot menu

C. nodeshell

D. SP prompt

Correct Answer: A Section: (none)

QUESTION 9

A volume was accidentally deleted two hours ago by another administrator. No backups exist.

In this scenario, what do you do to restore the data?

A. Use the ONTAP System Manager to recover the volume.

B. Use a volume snapshot to return the data to the active file system.

C. Use the volume recovery queue to restore the volume.

D. Use an aggregate snapshot to revert the aggregate to an earlier state.

Correct Answer: C Section: (none)

Reference: http://docs.netapp.com/ontap-9/index.jsp?topic=%2Fcom.netapp.doc.dot-cm-vsmg%2FGUIDD4E85AB5-EEBB-44B4-A648-5B1B04FD5F85.html

QUESTION 10

A customer is showing disk utilization is at 100% in Active IQ even though there are low protocol operations on the controller. You review the data shown in the exhibit.

```
disk              ut%   xfers   ureads--chain-usecs writes--chain-usecs
/aggr0/plex0/rg0:
  6b.34             1    2.18    0.17   1.00 10700   0.98 13.49   490
  6a.19             1    2.35    0.17   1.00 36600   1.15 11.83   504
  6a.45            13   17.98   16.88   2.13  5810   0.53  8.81   887
  6b.18            13   17.57   16.55   2.17  5357   0.42 11.00  1189
  6a.29            12   16.70   15.30   2.15  5820   0.60  6.75  1996
  6b.25            13   18.31   17.13   2.17  5611   0.48  7.59  1709
  6b.39           100   15.44   15.07   2.22 191927  0.00  ....     .
  6a.17            12   16.75   15.52   2.10  6126   0.50  8.63  1475
  6b.38            12   16.98   15.95   2.09  5614   0.43  9.92  1349
```

In this situation, what should you do?

A. Replace disks 6b.34 and 6a.19.

B. Add disks to the aggregate to bring down the average utilization.

C. Replace disk 6b.39.

D. Reseat shelf module B.

Correct Answer: C Section: (none)

NS0-194 VCE Dumps   **NS0-194 Exam Questions**   **NS0-194 Braindumps**